

# 910 COAXIAL CABLES

COAXIAL 10,1 MM, 11DB/100M 800 MHZ, 250M



Code : **9100057**

Model : **CL-201**

**Description**

RG-11 coaxial cable with physically expanded dielectric. Flameretardant. Conforms to norm EN 50117.

**Applications**

Used to transmit the TV signal in the terrestrial band or in the satellite IF band in distributions requiring substantial lengths of cable.

**Characteristics**

Supplied in coils of 250 m and packed in a carton box.

CODE		9100057	
MODEL		CL-201	
Internal conductor	Mat		CU
	mmø		1.63
Dielectric	Mat		PEE Physical
	mmø		7.20
Shielding	Mat		AL-PL-AL
Mesh	Mat		AL
Cover	Mat		PE black
	mmø		10
Attenuation / 100m	dB	50 MHz	2.7
		470 MHz	7.6
		862 MHz	11.0
		2150 MHz	20.0
Return loss	dB	5-470 MHz	>23
		470-2150 MHz	>20
Resistance to DC current	Ω/Km		34
Minimum bending radius	mm		35
Characteristic impedance	Ω		75 ±3,0
Units per packing			250
Packing weight	Kg		21
Packing dimensions	mm		400 x 400 x 370

CU - Cobre  
AL - Aluminio

PL - Poliéster  
PEE - Polietileno expandido

PVC - Policloruro de vinilo  
PE - Polietileno

CCA -Aluminio cobreado  
CCS -Acero cobreado

BOPP - Polipropileno biorientado  
PET - Tereftalato de polietileno

CÓDIGO CODE CODE	MODELO MODEL MODÈLE	CLASE DE APANTALLAMIENTO SHIELDING CLASS BLINDAGE CLASSE	EUROCLASE REACTION TO FIRE CPR EUROCLASSE
9100021	CE-753	A	Eca
9100056	CE-743		
9100058	CE-754	B	
9100068	CE-763	A	Dca s1,d0,a1
9100074	CE-764		
9100064	CE-140		
9100063	CE-150		
9100060	CE-860		
9100057	CL-201		