

910 COAXIAL CABLES

COAXIAL 10,1 MM, 11DB/100M 800 MHZ, 250M



Code : **9100057**

Model : **CL-201**

Description

RG-11 coaxial cable with physically expanded dielectric. Flameretardant. Conforms to norm EN 50117.

Applications

Used to transmit the TV signal in the terrestrial band or in the satellite IF band in distributions requiring substantial lengths of cable.

Characteristics

Supplied in coils of 250 m and packed in a carton box.

CODE		9100057	
MODEL		CL-201	
Internal conductor	Mat		CU
	mmø		1.63
Dielectric	Mat		PEE Physical
	mmø		7.20
Shielding	Mat		AL-PL-AL
Mesh	Mat		AL
Cover	Mat		PE black
	mmø		10
Attenuation / 100m	dB	50 MHz	2.7
		470 MHz	7.6
		862 MHz	11.0
		2150 MHz	20.0
Return loss	dB	5-470 MHz	>23
		470-2150 MHz	>20
Resistance to DC current	Ω/Km		34
Minimum bending radius	mm		35
Characteristic impedance	Ω		75 ±3,0
Units per packing			250
Packing weight	Kg		21
Packing dimensions	mm		400 x 400 x 370

CU - Cobre
AL - Aluminio

PL - Poliéster
PEE - Polietileno expandido

PVC - Policloruro de vinilo
PE - Polietileno

CCA -Aluminio cobreado
CCS -Acero cobreado

BOPP - Polipropileno biorientado
PET - Tereftalato de polietileno

CÓDIGO CODE CODE	MODELO MODEL MODÈLE	CLASE DE APANTALLAMIENTO SHIELDING CLASS BLINDAGE CLASSE	EUROCLASE REACTION TO FIRE CPR EUROCLASSE
9100021	CE-753	A	Eca
9100056	CE-743		
9100058	CE-754	B	
9100068	CE-763	A	Dca s1,d0,a1
9100074	CE-764		
9100064	CE-140		Fca
9100063	CE-150		
9100060	CE-860		Eca
9100057	CL-201		