

# 910 COAXIAL CABLES

COAXIAL 6,8 MM, 18DB/100M 800 MHZ, 100 M



Code : **9100060**

Model : **CE-860**

**Description**

Coaxial cable with triple shielding, physically expanded dielectric. Flame-retardant, conforms to norms EN 50265 and EN 50266.

**Applications**

Used to transmit the TV signal in CATV networks, in the terrestrial band.

**Characteristics**

Supplied in coils of 100 m.

CODE		9100060	
MODEL		CE-860	
Internal conductor	Mat		CSS
	mmØ		1,02
Dielectric	Mat		PEE Physical
	mmØ		4,60
Internal shielding	Mat		AL - Pet - AL
Mesh	Mat		AL
External shielding	Mat		AL - Pet - AL
Cover	Mat		PVC white
	mmØ		7,10
Attenuation / 100 m	dB	50 MHz	4,5
		470 MHz	13,8
		862 MHz	19,5
		2150 MHz	33,0
Return loss	dB	30 - 470 MHz	20,0
		470 - 1000 MHz	18,0
Resistance to DC current	Ω/Km		≤ 104
Minimum bending radius	mm		35
Characteristic impedance	Ω		75 ± 3
Units per packing	m		100
Packing weight	Kg		5,0
Packing dimensions	mm		330 x 330 x 100

CU - Cobre  
AL - Aluminio

PL - Poliéster  
PEE - Polietileno expandido

PVC - Policloruro de vinilo  
PE - Polietileno

CCA -Aluminio cobreado  
CCS -Acero cobreado

BOPP - Polipropileno biorientado  
PET - Tereftalato de polietileno

CÓDIGO CODE CODE	MODELO MODEL MODÈLE	CLASE DE APANTALLAMIENTO SHIELDING CLASS BLINDAGE CLASSE	EUROCLASE REACTION TO FIRE CPR EUROCLASSE
9100021	CE-753	A	Eca
9100056	CE-743		
9100058	CE-754	B	
9100068	CE-763	A	Dca s1,d0,a1
9100074	CE-764		
9100064	CE-140		
9100063	CE-150		
9100060	CE-860		
9100057	CL-201		