

912 TV-SAT AND MODULATOR EQUIPMENT

POWER SUPPLY 65 W (90-260 VAC)



Code : **9120168**

Model : **FA-312**

Description

Switching power supply, which permits the installation of an amplifier and different modules on the support frame. Power supply with a flat cable of 20 lines for different feed voltages.

Applications

Required for feeding the modules of the equipment.

Characteristics

Protected against power surges, overloads and short-circuits. Zamak chassis with side gills to facilitate proper ventilation. Supplied with power cable.

| CODE | 9120245 | | 9120249 | | 9120168 | | | | |
|------------------------------------|---------------------------|---|---------|--|---------|------------------|------|-------|-----|
| MODEL | | FA-410 | | FA-411 | | FA-312 | | | |
| Output voltage | V $\overline{\text{---}}$ | +3.3 | +5.2 | +12.0 | +24 | +3.3 | +5.2 | +12.0 | +24 |
| | mA | 5500 | 2500 | 1500 | 500 | 10000 | 5000 | 1500 | 500 |
| Peak to peak ripple voltage | mV | >50 | | | | 100 | | | |
| Mains voltage | V \sim | 230 \pm 20% 50/60 Hz 240 \pm 15% 50/60 Hz -20% 50/60 Hz | | 110 \pm 10% 50/60 Hz 127 \pm 10% 50/60 Hz | | 90..264 50/60 Hz | | | |
| | W | 72 | | | | 85 | | | |
| Operating temp. close to equipment | $^{\circ}$ C | -10..+65 | | | | | | | |
| Room temperature with/without fan | $^{\circ}$ C | -10..+55/+45 | | | | | | | |
| Protection index | | IP 20C | | | | | | | |
| Units per packaging | | 1 | | | | | | | |
| Packing weight | Kg | 1.43 | | | | 1.65 | | | |
| Packing dimensions | mm | 270 x 165 x 60 | | | | | | | |