

# 912 TV-SAT AND MODULATOR EQUIPMENT

## DVB-S2 DVB-T DOUBLE TRANSMOD CI DISEQC



Code : **9120201**

Model : **TT-411**

### Description

Transmodulator of encrypted satellite digital television services to terrestrial digital television with DiSEqC. Each module selects the services of one or two DVB-S/S2 satellite transponder and includes them in a DVB-T channels. Equipped with a Common Interface slot for insertion of the CAM and the subscriber's card. Programmable using PC software and a wireless programmer.

### Applications

Collective terrestrial digital television installations where the aim is to distribute encrypted satellite television services while avoiding the installation of satellite receivers. Allows channels from different satellites to be selected thanks to its DiSEqC control. Compatible with all collective TV installations since the channels can be distributed throughout the terrestrial band.

### Characteristics

Automatic error-detection system which greatly reduces maintenance work on the installation. Generated output channels of outstanding quality. Does not include the CAM or the decoder card. Zamak chassis with metal side panels. F-type connectors. The equipment can be assembled quickly and easily.

CODE		9120201
MODEL		TT-411
TV system		DVB-S / DVB-S2 → DVB-T/DVB-H EN 300421 EN 302307 EN 300744
Connection		F Female
Number of inputs		1 with duplexing or 2 independents
DVB-S/S2 receiver		
Frequency range	MHz	950 – 2150
Frequency step	KHz	1
LNB power supply	V---	DiSEqC 2.0 +13/+18 (0/22KHz)
	mA	350 max.
Symbol rate	Mbaud	1..45
Diplexing through loss		1,0±0,2
DVB-S2 receiver		
Input level	dB $\mu$ V	45..95
	dBm	-63..-13
F.E.C. QPSK		Auto, 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 DVB: EN 302307
F.E.C. 8PSK		Auto, 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 DVB: EN 302307
Roll-Off	dB	0,35/0,25/0,20
DVB-S receiver		
Input level	dB $\mu$ V	40..95
	dBm	-68..-13
F.E.C. QPSK		Auto, 1/2, 2/3, 3/4, 5/6, 7/8 DVB: EN 302307

Conditional access				
Standard		DVB-CI EN 50221 Common Interface		
Compatibility		Viaccess, Mediaguard, Videoguard, Seca, Betacryp, Nagravision, Irdeto, Cryptoworks, Conax		
COFDM modulator				
TV system		DVB-T/DVB-H EN 300744		
Output offset	MHz	-1/6, -1/8, 0, +1/8, +1/6 DVB-T		
Mode		2K, 8K, 4K (DVB-H) DVB: EN 300744		
Modulation		QPSK, 16QAM, 64QAM DVB: EN 300744		
F.E.C.		1/2, 2/3, 3/4, 5/6, 7/8 DVB: EN 300744		
Guard interval		1/2, 1/8, 1/16, 1/32 DVB: EN 300744		
MER	dB	39±2,0		
RF output				
Frequency range	MHz	47-862		
Frequency step	MHz	0,25		
Output level	dBµV	80±2,0		
Output level adjust	dB	20		
Bandwidth per channel	MHz	8, 7, 6, 5 DVB-H		
Through loss in the mixture	dB	0,9±1		
General features				
	V	+3.3	+5.2	+12
	mA	1300	550+CAM	55+LNB
Operating T close to equipment	°C	-10..+65		
Room T with/without fan	°C	-10..+55/+45		
Protection index		IP 30		
Units per packing		1		
Packing weight	Kg	1,4		
Packing dimensions	mm	265 x 165 x 40		