

# 912 TV-SAT AND MODULATOR EQUIPMENT

## POWER SUPPLY 50 W (230/240 VAC)



Code : **9120245**

Model : **FA-410**

### Description

Switching power supply, which permits the installation of an amplifier and different modules on the support frame. Power supply with a flat cable of 20 lines for different feed voltages.

### Applications

Required for feeding the modules of the equipment.

### Characteristics

Protected against power surges, overloads and short-circuits. Zamak chassis with side gills to facilitate proper ventilation. Supplied with power cable.

| CODE                                 |                           | 9120245   |      | 9120249  |     | 9120168          |      |       |     |
|--------------------------------------|---------------------------|---|------|--|-----|------------------|------|-------|-----|
| MODEL                                |                           | FA-410  |      | FA-411   |     | FA-312           |      |       |     |
| Output voltage                       | V $\overline{\text{---}}$ | +3.3  | +5.2 | +12.0  | +24 | +3.3             | +5.2 | +12.0 | +24 |
|                                      | mA                        | 5500  | 2500 | 1500   | 500 | 10000            | 5000 | 1500  | 500 |
| Peak to peak ripple voltage          | mV                        | >50   |      |  |     | 100              |      |       |     |
| Mains voltage                        | V $\sim$                  | 230 $\pm$ 20% 50/60 Hz<br>240 $\pm$ 15% 50/60 Hz<br>-20% 50/60 Hz |      | 110 $\pm$ 10% 50/60 Hz<br>127 $\pm$ 10% 50/60 Hz |     | 90..264 50/60 Hz |      |       |     |
|                                      | W                         | 72  |      |  |     | 85               |      |       |     |
| Operating temp. close to equipment   | °C                        | -10..+65  |      |  |     |                  |      |       |     |
| Room tmperature with/<br>without fan | °C                        | -10..+55/+45  |      |  |     |                  |      |       |     |
| Protection index                     |                           | IP 20C  |      |  |     |                  |      |       |     |
| Units per packaging                  |                           | 1   |      |  |     |                  |      |       |     |
| Packing weight                       | Kg                        | 1.43  |      |  |     | 1.65             |      |       |     |
| Packing dimensions                   | mm                        | 270 x 165 x 60  |      |  |     |                  |      |       |     |