

# 913 MULTISWITCHES

---

## 13X20 CASCADABLE MULTISWITCH

Code : **9130117**

Model : **ML-305**

### Description

Cascadable multiswitches for 12 polarities and terrestrial TV with 20, 24 and 32 outputs. The outputs are amplified in the satellite IF band. In the terrestrial band they can be configured to function in either active or passive mode. Need to be powered from each individual receiver so that the switching and amplification of each derived output will function.

### Applications

edium-sized collective satellite and terrestrial TV installations. It is essential that they be mounted along with end multiswitches, so as to obtain distributions of up to 128 outlets on a single line if they are installed with intermediary amplifiers.

### Characteristics

Shielded metal chassis with plastic supports. F-type connectors. Earth.

CODE	9130117		9130118		9130173	
MODEL	ML-305		ML-306		ML-308	
TV system	FM-TV / DVBS / AM-TV / DVB-T					
Connection	F female					
Inputs/outputs	13/13					
Tap outputs	20		24		32	
Frequency range	MHz	47-862	950-2150	47-862	950-2150	47-862 950-2150
<b>PASSIVE MODE</b>						
Tap loss	dB±TOL	26 ±2.0	2 ±2.0	26 ±2.0	2 ±2.0	26 ±2.0 4 ±2.0
Output level	dBµV	-	100 (IMD <sub>3</sub> -35 dB) 90 (IMD <sub>2</sub> -35 dB)	-	100 (IMD <sub>3</sub> -35 dB) 90 (IMD <sub>2</sub> -35 dB)	- 100 (IMD <sub>3</sub> -35 dB) 90 (IMD <sub>2</sub> -35 dB)
<b>ACTIVE MODE</b>						
Tap loss	dB±TOL	6 ±2.0	2 ±2.0	6 ±2.0	2 ±2.0	6 ±2.0 4 ±2.0
Output level	dBµV	95 (DIN 45004B)	100 (IMD <sub>3</sub> -35 dB) 90 (IMD <sub>2</sub> -35 dB)	95 (DIN 45004B)	100 (IMD <sub>3</sub> -35 dB) 90 (IMD <sub>2</sub> -35 dB)	95 (DIN 45004B) 100 (IMD <sub>3</sub> -35 dB) 90 (IMD <sub>2</sub> -35 dB)
<b>ACTIVE / PASSIVE MODE</b>						
Tap equalization	dB	1	2	1	2	1 2
Rejection between bands	dB	> 25 TV/SAT > 65 SAT/TV				
Isolation between users	dB	> 25 TV > 30 SAT				
Isolation of switching	dB	> 30 SAT/SAT				
Switching the outputs		DiSEqC 2.0 14V $\overline{\text{---}}$ / 18V $\overline{\text{---}}$ 0/22 kHz				
Power supply of the LNB		2050 mA / 13 V $\overline{\text{---}}$				
Output voltage	V $\overline{\text{---}}$	13 V $\overline{\text{---}}$				
Consumption from the receiver	mA	42 ±2.0 (14/18V $\overline{\text{---}}$ )				
Operating temperature close to equipment	°C	-10..+65				
Room temperature with/without fan	°C	-10..+55/+45				
Protection index		IP 30				
Units per packing		1	5	1	5	1 5
Packing weight	Kg	1.35	7.25	1.45	7.75	1.55 15.5
Packing dimensions	mm	395 x 245 x 55	340 x 290 x 260	395 x 245 x 55	340 x 290 x 260	333 x 315 x 44 355 x 335 x 460