

913 MULTISWITCHES

17X8 CASCADABLE MULTISWITCH

Code : **9130134**

Model : **ML-402**

Description

Cascadable multiswitches for 16 polarities and terrestrial TV with 8, 12 and 16 outputs. The outputs are amplified in the satellite IF band. In the terrestrial band they can be configured to function in either active or passive mode. Need to be powered from each individual receiver so that the switching and amplification of each derived output will function.

Applications

Medium-sized collective satellite and terrestrial TV installations. It is essential that they be mounted along with end multiswitches, so as to obtain distributions of up to 64 outlets on a single line if they are installed with intermediary amplifiers.

Characteristics

Shielded metal chassis with plastic supports. F-type connectors. Earth.

CODE	9130134		9130135		9130136	
MODEL	ML-402		ML-403		ML-404	
TV system	FM-TV / DVB-S / AM-TV / DVB-T					
Connection	F female					
Inputs	17/17					
Tap outputs	8		12		16	
Frequency range	MHz	47-862	950-2150	47-862	950-2150	47-862 950-2150
PASSIVE MODE						
Tap loss	dB±TOL	22 ±2.0	0 ±2.0	24 ±2.0	1 ±2.0	24 ±2.0 1 ±2.0
Output level	dBµV	-	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	-	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	- 100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)
ACTIVE MODE						
Tap loss	dB±TOL	2 ±2.0	0 ±2.0	4 ±2.0	1 ±2.0	4 ±2.0 1 ±2.0
Output level	dBµV	99 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	96 (DIN 45004B)	100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)	96 (DIN 45004B) 100 (IMD ₃ -35 dB) 90 (IMD ₂ -35 dB)
ACTIVE / PASSIVE MODE						
Tap equalization	dB	3	3	2	3	2 3
Throughgt loss	dB±TOL	4.5 ±1.0	2.0 ±1.0	4.5 ±1.0	3.0 ±1.0	4.5 ±1.0 4.0 ±1.0
Rejection between bands	dB	> 25 TV/SAT > 65 SAT/TV				
Isolation between users	dB	> 25 TV > 30 SAT				
Isolation of switching	dB	> 30 SAT/SAT				
Switching the outputs		DiSEqC 2.0 14V $\overline{\overline{\text{---}}}$ /18V $\overline{\overline{\text{---}}}$ 0/22 kHz				
Power supply of the LNB		2050 mA /13 V $\overline{\overline{\text{---}}}$				
Output voltage	V $\overline{\overline{\text{---}}}$	13 V $\overline{\overline{\text{---}}}$				
Consumption from the receiver	mA	42 ±2.0 (14/18V $\overline{\overline{\text{---}}}$)				
Operating temperature close to equipment	°C	-10..+65				
Room temperature with/without fan	°C	-10..+55/+45				
Protection index		IP 30				
Units per packing		1	5	1	5	1 5
Packing weight	Kg	1.05	5.65	1.05	5.65	1.20 6.40
Packing dimensions	mm	335 x 245 x 55	345 x 290 x 260	335 x 245 x 55	340 x 290 x 260	335 x 245 x 55 340 x 290 x 260