



CODE		9180008			
MODEL		FSM-640			
<b>RF input</b>					
Terrestrial frequency range	MHz	5-900			
Satellite frequency range	MHz	900-2200			
Resolution	KHz	Terrestrial 50 KHz sampling 1 KHz Satellite 1 KHz sampling 1 KHz			
Tuning mode		Channel / Frequency			
Search mode		Manual / Automatic			
Standards		B, G, D, K, I, L, M, N, FM, PAL, SECAM, NTSC, DVB-T/H, DVB-T2, DVB-S, DVB-S2, DSS			
Impedance	$\Omega$	75			
Connection		F male with F-F, F-BNC adapters			
Remote supply	V $\overline{=}$	5	13	18	24
	mA	500	500	500	300
LNB supply		13-18V /0-22Khz /DiSEqC 1.2			
Dynamic level range	dB $\mu$ V	20..120 (terrestrial) - 30..110 (sat)			
<b>Analog measurements</b>					
Terrestrial band		Signal level, Carrier to noise (C/N), video/audio ratio			
Satellite band		Signal level, C/N			
<b>Digital measurements</b>					
DVB-T/H		Signal level, C/N, MER, VBER, CBER, UNC, echoes analyzer and constellation			
DVB-T2		Signal level, C/N, MER, LDPC, BCH, FER, echoes analyzer and constellation			
DVB-S		Signal level, C/N, MER, VBER, CBER, UNC and constellation diagram			

<b>CODE</b>		9180008
<b>MODEL</b>		FSM-640
<b>Spectrum</b>		
Ultra fast analysis mode	ms	350 (3 times for s)
Span	MHz	5.. full
Display graphics		60 dB (10dB/div)
Attenuation		0..50dB automatic
<b>Display</b>		
Display type		16/9 LCD TFT 10" tactile
Resolution		1280x800
Digital mode		SD (MPEG-2), HD (MPEG-4)
Audio		MPEG-1, MPEG-2, Dolby® Digital, Dolby® Digital Plus
Connection		HDMI for output audio, video
<b>Other specifications</b>		
Keyboards and cursor		Capacitive touchscreen
Ports		LAN RJ-45, USB, mini USB
Data storage		Non volatil memory, USB pendrive
<b>General features</b>		
Power supply		110/230Vac - 15V -6A adapter
Battery		LiOn 70W
Autonomy		4H typ.
Charging time		1,5 Hour for 80% capacity
Operatin temperature range	°C	-5.. 45
Units per packing		1
Packing weight	Kg	4,4
Packing dimensions	mm	336 x 444 x 148