

# 941 SENSORS AND ACTUATORS

## WALL UNIT NURSE CALL, PRESENCE & CONNECT

Code : **9410029**

Model : **LLC-102**



### Description

Room peripheral with connector for handset (LLC-11x), nurse call button with red LED indicator and nurse presence push-button with green LED indicator. Allows launching a call from the connected handset (LLC-21x) or from the red call button. It allows the nurse indicating that is in the room and thereby cancelling existing active call in the room. Once the call is initiated, the red LED indicator allows easy identification of the place from which the call was placed. When the nurse presses the button the green LED indicator stands steady ON until the presence finishes pressing the button again. Recessed or surface mounting.

9410029

LLC-102

### Especificaciones

Conector	Hembra miniDIN-8
Botón de llamada a enfermera	Color botón: Rojo (RAL 3020, rojo tráfico) Color indicador led: Rojo Icono: enfermera Color icono: blanco (RAL 9003, blanco señales)
Botón de presencia / cancelación	Color botón: Verde (RAL 6018, verde amarillento) Color indicador led: verde Icono: persona 1 Color icono: blanco (RAL 9003, blanco señales)
Alimentación	24 V
Consumo (reposo)	10 mA
Consumo (máximo)	40 mA
Dimensiones	80x 80x 30 mm
Peso	80g
Material	ABS / Policarbonato
Color (embellecedor)	Blanco (RAL 9001, blanco crema)
Temperatura de funcionamiento	5°C a 55°C
Protección	IP 42
Montaje	Empotrado (con ACC-100 / ACC-101) Superficial (con ACC-110)
Normativa (Seguridad)	EN 60950-1:2006
Normativa (Emisiones electromagnéticas)	EN 61000-3-3

