

# 941 SENSORS AND ACTUATORS

---

## WC PULLCORD IP65



Code : **9410104**

Model : **LLC-122**

### Description

Bathroom peripheral with 1.8m call pull cord with red LED for installation in humid environments (showers, saunas, etc.). It allows the patient to launch a call by pulling cord. Once the patient call has initiated a red LED allows easy identification of call state. It has an anti-strangulation mechanism to release the pull call mechanism preventing accidents and breakage of the device. It has a red pull at the bottom which allows the patient easy location of the pull. Flush mounting with universal box.

## Specifications

Call pull-cord	Switch type: reed contact
	Length: 1,8 m PVC antibacterial color red (RAL 3005 , wine red)
	Anti-strangulation mechanism 6Kg
	Pull cord pull (RAL 3005, red wine)
Power supply	24 VDC
Consumption (standby)	0 mA
Consumption (switch activation)	125 mA
Dimensions (width x height x depth)	80 x 80 x 20 mm
Weight	130g
Material	ABS / Polycarbonate
Color (trim)	White (RAL 9010, pure white)
Operating temperature	-5°C...55°C
Protection degree	IP 66
Cleaning	Resistant to cleaning agents according to EN 13727
Mounting	Mounted (standard box, installation depth 38mm ACC-100 / ACC-101)
Approvals	CE