

MANAGER SWITCH 16P 16+2 FO

Code : **9430030**

Model : SWI-133

Description

Switch with 16 ports at 10/100/1000 Mbps, providing a fast backbone and connecting servers and users, quickly transferring big multimedia files, images and video. It also includes 2 GBIC Small Form-factor Pluggable (SFP) hot swappable slots, that offer Optic Fiber connection for big distances. It allows the configuration of ports, links, VLANs and establishing priority traffic.

EXTERNAL I/O PORTS

16 ports 10/100/1000 10 base-T type IEEE 802.3, 100 base-Tx type IEEE 802.3u, 1000 base-T Gigabit Ethernet type IEEE 802.3ab.

2 dual personality ports puertos con doble personalidad: each one can be used as an RJ-45 10/100/1000Mbps or a mini-GBIC slot to be used with mini-GBIC transceivers.

| SPECIFICATIONS | |
|------------------------------|---|
| Latency | 1Gb a 1Gb < 20 µs. for 64 bytes architecture in store-and-forward mode |
| Size of the address book | 8000 inputs |
| Routing / switching capacity | 32Gbps. |
| Active flow control | Half-duplex back-pressure control. Full-duplex IEEE 802.3x pause frame flow control. |
| Priority | IEEE 802.1p, 802.1Q, 802.1D |
| Frame mounting | In 19" telco frame EIA standard |
| Power supply | 100-240VAC/50-60Hz universal connection |
| Energy consumption | Maximum 32W |
| Security | CE marked cUL 60950 (listed)/EN60950 (low voltage directive) |
| Dimensions | 440 x 205 x 43mm |
| Weight | 270g |
| CEM | CE marked FCC Parte 15 Class A. VCCI Class A. C-Tick. |