

941 SENSORS AND ACTUATORS

WC PULLCORD WITH CALL AND CANCELLATION



Code : **9410333**

Model : **LLC-124**

Description

Bathroom peripheral with pull-cord of call of 2m, push button with green LED indicator and cancellation button. Allows the user to launch a call by pulling the pull-cord or from the green call button. Once the patient call is initiated, the green LED indicator allows easy identification of call status. Product has an anti-strangle mechanism that allows the separation of the pull-cord into 2 parts avoiding accidents. The LLC-124 has a red ball at the lower end that allows the user to easily locate of the pull-cord. Recessed or superficial installation.

Applications

Designed to be installed in public areas such as accessible toilets and accessible locker rooms, an assistance call is transmitted which is perceptible from a control point or from a crowded pass. This device unit belongs to ACCUROrefugium system, which complies with Spanish building regulations DB-SUA9 included in CTE (Código Técnico de Edificación) mandatory since December 2017.

9410333

LLC-124

Specifications

Call pull-cord	Length: 2m red plastic
	Anti-strangulation mechanism 6Kg
	Pull-cord clip color red (RAL 3020, red traffic)
Call Button	Button color: Green (RAL 6018)
	LED indicator color: green
	Color icon: white (RAL 9003, white signal)
Cancel Button	Button color: (RAL 3020, red traffic)
	Icon: Cancellation
	Color icon: white (RAL 9003, white signal)
Power supply	24 V
Consumption (idle)	5 mA
Consumption (maximum)	20 mA
Dimensions	80x 80x 30 mm
Weight	80g
Housing	ABS + Polycarbonate
Colour	White (RAL 9001, cream)
Operating temperature	5..55 °C
Protection index	IP 42
Mounting	Recessed Mounting (with ACC-100 / ACC-101) Superficial (with ACC-110)
Safety conformity	EN 60065:2014
EMC conformity	EN 61000-6-3:2007/ A1:2012, EN 61000-6-1:2007