

912 TV-SAT AND MODULATOR EQUIPMENT

2XDVB-S/S2/T/T2 TO DVB-T/C TRANSMOD CI



Code : **9120253**

Model : **TM-112**

himalaya transmodulator of DVB-S/S2 satellite digital television services or DVB-T/T2 terrestrial digital television to DVB-T or DVB-C. Each module selects services from two DVB-S/S2 satellite transponders or DVB-T/T2 terrestrial channels and includes them in a DVB-T or DVB-C channel. Can be configured using a web browser in a computer connected via ethernet cable.

Equipped with a Common Interface slot for insertion of the CAM and the subscriber's card for encrypted services. Can be configured using a web browser in a computer connected via ethernet cable.

CÓDIGO-CODE-CODE		9120254	9120253	9120259
MODELO-MODEL-MODELE		TM-102	TM-112	TM-202
ENTRADA RF / RF INPUT / ENTRÉE RF				
Número de entradas Number of inputs Nombre d'entrées		1 con desmezcla o 2 independientes 1 with duplexing or 2 independent 1 avec découplage ou 2 indépendants		
Número de receptores Number of receivers Nombre de récepteurs		2		
Rango de frecuencia Frequency range Gamme de fréquences	MHz	DVB-T/T2 : 47 - 862 DVB-S / DVB-S2 : 950 -2150		
Alimentación LNB LNB power supply Alimentation LNB	V _{DC}	DiSEqC 2.0 13/18		
	mA	350		

CÓDIGO-CODE-CODE	9120254	9120253	9120259
MODELO-MODEL-MODELE	TM-102	TM-112	TM-202

PROCESADO TS / TS PROCESSING / TRAITEMENT TS

Adaptación PSI/SI PSI/SI adaptation Adaptation PSI / SI		Generar e insertar tablas: Generation and insertion of tables: Générer et insérer des tableaux : PAT, PMT, CAT, SDT, NIT, TDT, TOT, EIT	
Adaptación NIT NIT adaptation Adaptation NIT		Sí / Yes / Oui	
Gestión de LCN, TDT, TOT LCN, TDT, TOT management Gestion LCN, TDT, TOT		Sí / Yes / Oui	
Selección de PID PID selection Sélection PID		Sí / Yes / Oui	

ACCESO CONDICIONAL / CONDITIONAL ACCESS / ACCÈS CONDITIONNEL

Número de ranuras PCMCIA Number of PCMCIA slots Nombre d'emplacements PCMCIA		-	1	-
Norma Standard Norme		-	DVB-CI: EN 50221 (Common Interface)	-
Compatibilidad Compatibility Compatibilité		-	Viaccess, Mediaguard, Videoguard, Seca, Betacrypt, Nagravision, Irdeto, Cryptoworks, Conax	-

SALIDA RF / RF OUTPUT / SORTIE RF

Número de canales de salida Number of output channels Nombre de canaux de sortie			1	2
Rango de frecuencia Frequency range Gamme de fréquences	MHz	DVB-T/DVB-C : 47-862		
Nivel de salida Output level Niveau de sortie	dB μ V \pm TOL	80 \pm 2,0		