TAP-OFFS AND SPLITTERS

IF SPLITTER 2 OUT WITH DC PATH

Code : **9060097**

Model : **DI-203**

Description

2-way splitter for terrestrial and satellite TV, covering all frequencies from 5MHz to 2,400MHz. It distributes all the input signal in equal parts among the 2 outputs. It has a feed path through any of its 2 outputs to the input. The response of the outputs is flat. Also available in 3-, 4-, 6- or 8-way models.

Applications

Individual and collective installations of terrestrial and satellite TV with a star-shaped distribution. They permit power to be fed from a preamplifier or LNB through any of the outputs. In installations with multiswitches, a control voltage can be sent through their outputs.

Characteristics

Protection diodes in all the outputs. Shielded zamak chassis and metal plate. Zamak F-type connectors which form part of splitter chassis.

CÓDIGO-CODE-CODE			9060097	9060098	9060099	9060100	9060101
MODELO-MODEL-MODELE			DI-203	DI-303	DI-403	DI-603	DI-803
Conexión Connection Raccordement			F hembra F female F femelle				
Salidas Outputs Sorties			2	3	4	6	8
Rango de frecuencias Frequency range Gamme de fréquences	MHz		5 - 2400				
Atenuación de distribución Top loss Atténuation de répartition	dB	5-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz	4,5 4,5 6,0 6,0	7,5 8,0 10,5 11,0	8,5 8,5 10,5 11,5	10,5 11,5 15,0 16,5	12,5 13,0 16,5 17,5
Planitud en banda Flatness response Ondulation das la bande	dB		±0,3				
Planitud en canal Channel flatness response Ondulation das le canal	dB		±0,1				
Desacoplo Isolation Découplage	dB	5-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz	>18 >20 >18 >18	>19 >20 >20 >20	>20 >23 >18 >15	>22 >23 >20 >20	>22 >22 >20 >20
Pérdida de retorno Return loss Pertes de retour	dB	5-47 MHz 47-862 MHz 950-2150 MHz 2150-2400 MHz	>10 >10 >10 >10	>8 >10 >10 >10	>10 >13 >12 >13	>9 >10 >10 >10	>9 >9 >10 >10
Paso de corriente DC path Passage d'alimentation	V⎓ mA Tone		24 max 500 max 22KHz / DiSEqC				
Índice de protección Protection index Indice de protection			IP 20				
Unidades por embalaje Units per packing Unités per emballage			12				
Peso embalaje packing weight Poids emballage	Kg		1,36	1,55	1,65	2,88	2,93
Dimensiones embalaje Packing dimensions Dimensions emballage	mm		176 x 148 x 67	201 x 155 x 69	207 x 162 x 72	250 x 153 x 132	