

# 972 VIDEO DOOR ENTRY SYSTEM KITS

## ENARA KIT 1 BUTTON IBLACK

Code : **9720164**

Model : **KVS-50921**

### Description

ALCAD video door entry system kits Include all the necessary material to carry out the installation, with the exception of the cable. Include entrance panel for the building with video camera, power supply and indoor monitor. The installation can be completed with accessories, such as rainshields or decorative frames, and with different extensions, such as second entrance panel or monitors and additional telephones.

### ENARA monitor

This kit includes the ENARA monitor, which is the most compact monitor on the market. The compact size makes Enara the perfect monitor for replacements where space is limited. Its new neutral and minimalist design combines perfectly with any kind of decoration in your home, from the most classic to the most avant-garde.

The modern capacitive technology used for the touch buttons ensures a reliable and long-lasting operation, and as there are no electrical contacts or moving parts, the accumulation of dirt that affects the operation of traditional push-buttons is avoided.

The Enara monitor has a very useful function so that nobody interrupts your rest time: the "Don't disturb" function. Its large 4-inch flat screen allows you to identify the person making the call with total clarity and security and also, the on-screen menu allows you to adjust the image to achieve optimal performance in any lighting situation.



CODE		9720164
MODEL		KVS-50921
SYSTEM		2-wire
<b>ENARA MONITOR</b> <ul style="list-style-type: none"> <li>• Screen</li> <li>• On screen menu</li> <li>• Communication</li> <li>• Call volume set</li> <li>• Pushbuttons</li> <li>• Pushbutton for auxiliary functions</li> <li>• Image memory</li> <li>• Magnetic loop</li> <li>• Power supply</li> <li>• Consum</li> <li>• Working temperature</li> <li>• Connections</li> <li>• Tap-off and line termination load</li> <li>• Mounting</li> <li>• Dimensions</li> </ul>	Vdc mA °C	9630075 MVC-140 TFT Color 4" Yes Hands Free "Don't disturb"; "low"; "high" 4 touch pushbuttons 1 touch pushbutton NO NO Through the bus (12 ... 18Vdc) 25 mA (at rest); 360 mA (working) +5... +55 °C Pluggable terminals Yes, Configurable by means of microswitches Surface 120 x 168 x 22
<b>ENTRANCE PANEL</b> <ul style="list-style-type: none"> <li>• Look</li> <li>• Pushbuttons</li> <li>• Dimensions</li> <li>• Materials</li> <li>• IP rate protection</li> <li>• Camera</li> <li>• Night vision</li> <li>• View angle</li> <li>• Adjustable camera</li> <li>• Working temperature</li> </ul>	mm  ° ° °C	iBLACK 1 128 x 147 Aluminum and Polycarbonate IP54 CCD Color 1/3" White LEDs 60° (H); 45° (V) 10° in any direction -10°C ... +55°C
<b>FLUSH BOX FOR ENTRANCE PANEL</b> <ul style="list-style-type: none"> <li>• Dimensions</li> <li>• Material</li> </ul>		9740005 CMO-002 144 x 131 x 45 PVC
<b>POWER SUPPLY</b> <ul style="list-style-type: none"> <li>• Primary</li> <li>• Secondary</li> <li>• Protected against short circuits</li> <li>• Format</li> <li>• Mounting</li> <li>• Dimensions</li> <li>• Working temperature</li> </ul>	mm °C	9650004 ALS-020 230Vac; 50/60 Hz; 0,45A 18Vdc; 2A Yes, With LED indicator DIN rail 6 elements DIN Rail or Wall 105 x 90 x 60 -10°C ... +65°C
<b>ELECTRIC LOCK (Not included)</b> <ul style="list-style-type: none"> <li>• Suggested</li> <li>• Working Voltage</li> <li>• Maximum consumption</li> </ul>	Vdc mA	9730062 ABR-015 12 - 18 Vdc 500 mA
Packing weight	Kg	1,86 Kg
Packing dimensions	mm	300 x 140 x 270 mm