

941 SENSORS AND ACTUATORS

BED CALL UNIT CALL BUTTON & CONNECTOR

Code : **9410344**

Model : **LLC-801**

Bed unit with 1 button (call) and socket for connecting call handset (DIN8).



| CÓDIGO-CODE-CODE | 9410343 / 9410344 / 9410346 / 9410345 / 9410347 / 9410348 | 9410362 / 9410363 / 9410364 / 9410365 / 9410367 / 9410366 |
|---|--|---|
| MODELO-MODEL-MODÈLE | LLC-80X | LLC-90X |
| Conector de pera Hand Set connector Prise manipulateur/poire d'appel | DIN 8 | |
| Color de Botón Push button color Boutons couleur | Verde, Green, Vert: ,LLC-X02, LLC-X03, LLC-X04 Azul, Blue, Bleu: LLC-X03 Rojo, Red, Rouge: LLC-X01, LLC-X02, LLC-X03, LLC-X04, LLC-X05 Amarillo, Yellow, Jaune: LLC-X04 | |
| Alimentación Power supply Alimentation | 24V | |
| Consumo (stand by) Energy consumption (stand by) Consommation (stand by) | 10 mA | |
| Consumo (max.) Energy consumption (max.) Consommation (max.) | 40 mA | |
| Dimensiones Size Dimensions | 80x80x10mm | |
| Peso Weight Poids | 0,08Kg | |
| Material Material Matériel | ABS/Polycarbonate | |
| Color Color Couleur | Blanco, White, Blanc (RAL 9001) | |
| Temperatura operacional Operating temperature Température de fonctionnement | 5°C - 55°C | |
| Indice de protección Protection Indice de Protection | IP 42 | |
| Instalación Mounting Installation | Empotrado, Embedded, Encastré (ACC-100 / ACC-101) En superficie, On surface, En saillie (ACC-110) | |
| Normativa (seguridad) Normative (security) Norme (sécurité) | EN 60950-1:2006 | |
| Normativa (emisiones electromagnéticas) Normative (electromagnetic emissions) Norme (champs magnétique) | EN 61000-3-3 | |

