941 SENSORS AND ACTUATORS

BED UNIT WITH 3 BUTTONS & CONNECTOR



Code : **9410346**

Model : **LLC-803**

Description:
Touch-operated bed unit with three buttons (call, presence and code blue), female DIN-8 connector compatible with LLC-75x call handsets and three reassurance LEDs, one for each button. Easy to clean thanks to the antibacterial coating on its front panel. A call can be initiated using the red call button, presence can be registered using the green button and a code blue can be activated using the corresponding button. The red and blue LEDs indicate the status of the corresponding call. Flush-mounted or surface-mounted installation.

CÓDIGO-CODE-CODE	9410344 9410345 9410346	9410363 9410364 9410365
MODELO-MODEL-MODÈLE	LLC-80X	LLC-90X
Conector de pera Handset connector Prise manipulateur/poire d'appel	DIN 8	
Color de botón Push button color Boutons couleur	**Rojo, Red, Rouge:** LLC-X01, LLC-X02, LLC-X03 **Verde, Green, Vert:** LLC-X02, LLC-X03 **Azul, Blue, Bleu:** LLC-X03	
Alimentación Power supply Alimentation	24V	
Consumo (stand by) Energy consumption (stand by) Consommation (stand by)	10 mA	
Consumo (máx.) Energy consumption (max.) Consommation (max.)	40 mA	
Dimesiones Size Dimensions	80x80x10mm	
Peso Weight Poids	O,08Kg	
Material Material Matériel	ABS / Polycarbonate	
Carátula con recubrimiento antibacteriano Antibacterial front overlay Face avant adhésive antibactérienne	Sí / Yes / Oui	
Color Color Couleur	Blanco, White, Blanc (RAL 9001)	
Temperatura operacional Operating temperature Température de fonctionnement	5°C - 55°C	
Indice de protección Protection Indice de Protection	IP42	
Instalación Mounting Installation	Empotrado, Embedded, Encastré (ACC-100 / ACC-101) En superficie, Surface, En saillie (ACC-110)	
Normativa (seguridad) Normative (security) Norme (sécurité)	EN 60950-1:2006	
Normativa (emisiones electromagnéticas)		