

# 942 TELEPHONY

# SIP PHONE 7" SCREEN ANDROID



Code: 9420131

Model: TFI-361

## Description

TFI-361 is an Android-based multimedia terminal with a 7 inch touch screen and a 1.3M CMOS sensor camera. It supports H.264/H.263 codecs with adaptive bandwidth adjustment. The  $7\mbox{\ensuremath{\square}}$  touch screen offers excellent user experiences such as high quality videophone, smooth internet surfing,

Android Apps and daily information.

☐ AutoP: FTP/TFTP/HTTP/HTTPS

### Characteristics

Characteristics
7 inch capacitive touch screen TFT LCD, 1024*600 pixels
☐ 1.3M pixels CMOS camera with privacy shutter
$\hfill\square$ Dual switched 10/100/1000Mbps Ethernet ports, supporting IEEE802.11af
and IEEE802.az Energy Efficient Ethernet
☐ Built-in Bluetooth, USB and Wi-Fi feature
☐ Built-in Radio Frequency Module: support either 868MHz or 433MHz
Android 5.1 Operating System and support Android API for the 3rd party
Android application installation
Uvoice and Video Codec: PCMA,PCMU, G.722, G.723, G.729, H.263,
H.264
☐ Protocol: SIP RFC3261, TCP/UDP/IP, PPPoE, RTP/RTCP, HTTP/HTTPS, etc



CODE	9420131
MODEL	TFI-361
Video Features	<ul> <li>Video Codec: H.263,H.264</li> <li>Video Solution: QCIF, CIF, VGA, 4CIF, 720P</li> <li>Video Bitrate: 64kbps-2Mbps</li> <li>Adaptive Bandwidth Adjustment</li> <li>Video Character: PIP, Full Screen, Local Video ON/OFF Control</li> <li>Image Codec: JPEG, GIF, PNG, BMP</li> </ul>
Audio Features	<ul> <li>Wideband Audio Codec: G.722</li> <li>Narrowband Audio Codec: PCMA,PCMU, G.723, G.729</li> <li>VAD</li> <li>CNG</li> <li>Echo Canceller G.165/G.168</li> <li>Full-Duplex Speakerphone</li> <li>4 DTMF modes: RFC2833,In-Band, SIP INFO, Auto</li> </ul>
Network and Security	<ul> <li>SIP V2(RFC3261)</li> <li>UDP/TCP/IP</li> <li>RTP/RTCP</li> <li>ARP/RARP</li> <li>NAT Traversal: Static NAT configure, SIP Keep Alive</li> <li>IP Assignment: Static IP, DHCP, PPPoE</li> <li>NTP For Auto Time Setting</li> <li>Network Packet Capture</li> <li>TFTP/FTP/HTTP/HTTPS Client API</li> <li>QoS: Layer 2 (802.1Q, 802.1p) and Layer 3 (ToS, DiffServ)</li> <li>HTTPS</li> <li>MD5 and MD5-sess Based Authentication</li> <li>Access for Administration</li> </ul>



CODE	9420131
MODEL	TFI-361
Phone Features	<ul> <li>Android 5.1 Operation System</li> <li>Support 6 SIP accounts</li> <li>Call Waiting</li> <li>Call Transfer</li> <li>Call Hold</li> <li>Mute</li> <li>Redial</li> <li>Speed Dial</li> <li>Direct IP call</li> <li>6-Way Conference</li> <li>DND (Do Not Disturb)</li> <li>Volume Adjustable</li> <li>Ring Tones Selectable</li> <li>Multi-Languages Support</li> <li>Default Apps: Phonebook, Weather, Google Play, Digital Photo Frame, Stock, News Feeds, Calendar, World Clock, Alarm Clock, Email, Camera, File Browser, Games.</li> <li>3rd Party Android Applications</li> </ul>
Directory	<ul> <li>Local Phonebook up to 3000 Groups</li> <li>Phonebook with Contact Picture</li> <li>Favorites</li> <li>Blacklist</li> <li>Call Logs: 600 Entries (200 Missed Calls; 200 Dialed Calls; 200 Received Calls.)</li> <li>LDAP</li> <li>Intelligent Search Method</li> </ul>
Management	<ul> <li>Firmware Local Update: USB Flash Disk</li> <li>Firmware Remote Update: FTP method</li> <li>Auto Provisioning Using FTP/TFTP/HTTPS</li> <li>System Log Export</li> <li>Restore To Factory Default</li> <li>Configuration Managements Via LCD</li> </ul>
Physical Features	<ul> <li>7 Inch Capacitive Touch Screen, Resolution 1024*600, 16:9 Wide Screen Aspect Ratio</li> <li>3 LED Lights (1 Power Light, 1 Network Light, and 1 Message Light)</li> <li>28 Keys</li> <li>RK3288 Chipset</li> <li>Flash Memory 8GB</li> <li>2GB DDR3 Memory</li> <li>Foot Stand</li> <li>1.3 Mega Pixels CMOS Camera, Free Rotation</li> <li>RJ9 Handset</li> <li>3.5mm Headset jack</li> <li>2 RJ45 10/100/1000M Ethernet Jacks</li> <li>Energy Efficient Ethernet: IEEE802.3az</li> <li>Power over Ethernet: IEEE802.3af</li> <li>868MHz or 433MHz RF Module</li> <li>Bluetooth</li> <li>Wireless Access: 802.11b/g/n</li> <li>1 USB 2.0</li> <li>1 HDMI Video Out Port</li> <li>Power Adapter: AC 100~240V Input, DC 12V/1A Output</li> <li>Dimensions: 240*192*106mm</li> <li>Operating Temperature: 32° ~ 104°F (0~ 40°C)</li> </ul>