# 941 SENSORS AND ACTUATORS

## PRESENCE 1ST, 2ND, CALL & BLUE CODE BUT.




Code : **9410353**

Model : **LLC-832**

Description:
Touch-operated bed unit with four buttons (call, presence 1, presence 2 and code blue) and four reassurance LEDs, one for each button. Easy to clean thanks to the antibacterial coating on its front panel. A call can be initiated using the red button, two types of presence can be registered using the corresponding buttons, and a code blue can be activated. Both the red and blue LEDs indicate the status of the corresponding call. Flush-mounted or surface-mounted installation.

| CÓDIGO-CODE-CODE | 9410352, 9410351, 9410353, 9410360, 9410354, 9410355, 9410356, 9410357, 9410358, 9410359 | 9410370, 9410371, 9410372, 9410373, 9410374, 9410375, 9410376, 9410377, 9410378, |
|---|---|---|
| MODELO-MODEL-MODÈLE | LLC-83X, LLC-84X | LLC-93X, LLC-94X |
| Color de Botón<br>Push button color<br>Boutons couleur | **Verde, Green, Vert:** LLC-X30, LLC-X31, LLC-X32, LLC-X42, LLC-X43<br>**Azul, Blue, Bleu:** LLC-X32, LLC-X41, LLC-X43, LLC-X47<br>**Rojo, Red, Rouge:** LLC-X32, LLC-833, LLC-X40, LLC-X42, LLC-X48<br>**Amarillo, Yellow, Jaune:** LLC-X31, LLC-X32 | |
| Alimentación<br>Power supply<br>Alimentation | 24V | |
| Consumo (stand by)<br>Energy consumption (stand by)<br>Consommation (stand by) | 10 mA | |
| Consumo (max.)<br>Energy consumption (max.)<br>Consommation (max.) | 40 mA | |
| Dimesiones<br>Size<br>Dimensions | 80x80x10mm | |
| Peso<br>Weight<br>Poids | O,08Kg | |
| Material<br>Material<br>Matériel | ABS/Polycarbonate | |
| Color<br>Color<br>Couleur | Blanco, White, Blanc (RAL 9001) | |
| Temperatura operacional<br>Operating temperature<br>Température de fonctionnement | 5°C - 55°C | |
| Indice de protección<br>Protection<br>Indice de Protection | IP 42 | |
| Instalación<br>Mounting<br>Installation | Empotrado, Embedded, Encastré (ACC-100 / ACC-101)<br>En superficie, On surface, En saillie (ACC-110) | |
| Normativa (seguridad)<br>Normative (security)<br>Norme (sécurité) | EN 60950-1:2006 | |
| Normativa (emisiones electromagneticas)<br>Normative (electromagnetic emissions)<br>Norme (champs magnétique) | EN 61000-3-3 | |
| Conector de red<br>Net Connector<br>Connexion | Bornas, Contact: 8XX | RJ45: LLC-9XX |