

942 TELEPHONY

4-LINE IP PHONE, BACKLIT TFT



Code : **9420133**

Model : **TFI-402**

The TFI-402 is a state-of-the-art, full-featured IP desk phones for small or large scale deployments suitable for use in a multitude of business scenarios. Supporting four SIP identities and five programmable keys with built in LEDs for visual call indication alerts, the TFI-402 blends an elegant utilitarian design for high usability with high performance and affordability. It is a easy-to-use telephone with functionality such as call ID, call waiting, call register, call transfers (attended and unattended) and volume control, which allow its use by the staff as a telephone control station for the reception of calls from the rooms.

CODE	9420133
MODEL	TFI-402
AUDIO FEATURE	Codecs: <ul style="list-style-type: none"> · G.711 a-law, μ-law · G.722 (wideband) · G.726, g.729ab, gsm 6.10 (fr) · 10 built-in assignable ringtones · Comfort noise generator (cng) · Voice activity detection (vad)
NETWORK & SECURITY	<ul style="list-style-type: none"> · 802.1X Authentication and EAPOL · Transport layer security (TLS) · SRTP (RFC3711), SIPS, RTCP <ul style="list-style-type: none"> · HTTPS server/client · Password-protected web interface <ul style="list-style-type: none"> · VPN support · VLAN (IEEE 802.1Q) · LLDP-MED, RTCP-XR
CALL FEATURES	<ul style="list-style-type: none"> · Speed dialing · URL dialing · Local dial plan · Automatic redial on busy · Call completion (busy/unreachable) <ul style="list-style-type: none"> · Caller identification · Call waiting · Call blocking (deny list) <ul style="list-style-type: none"> · Auto answer · Hold · Music on hold(2) · Handling of up to 4 simultaneous calls <ul style="list-style-type: none"> · Blind and attended transfer · Call forwarding · 3-way conferencing on the phone · Extension monitoring, call pickup(2) <ul style="list-style-type: none"> · Call park, call unpark(2) · Multicast paging · DND mode (do not disturb) <ul style="list-style-type: none"> · Keyboard lock · Client matter code (CMC)(2) · Unified communications ready

CODE	9420133
MODEL	TFI-402
PHISICAL FEATURES	<ul style="list-style-type: none"> · Dimensions (approx.): <ul style="list-style-type: none"> · 205 x 185 x 40 mm (LxWxD) w/o footstand · 205 x 185 x 200/220 mm (LxWxD) with footstand · Weight (approx.): device 440 g, footstand 120 g <ul style="list-style-type: none"> · Input voltage: 5 Vdc (SELV) · Power supply: PoE or 5Vdc power adapter (1) <ul style="list-style-type: none"> · Handset: 4P4C connector · Headset: 4P4C · Hearing aid compatible (HAC) handset <ul style="list-style-type: none"> · Environmental conditions: <ul style="list-style-type: none"> · Ambient temperature: 0°C to 35°C (32°F to 95°F) · Storage temperature: -10°C to 45°C (14°F to 113°F) · Humidity: 5% to 95% (non-condensing) · Included in delivery: <ul style="list-style-type: none"> · Phone unit · Footstand · Handset with cord · Ethernet cable · Quick Installation Guide · Color: black · Warranty: 2 Years