941 SENSORS AND ACTUATORS

BED UNIT WITH 3 BUTTONS & CONNECTOR

Code : **9410365**

Model : **LLC-903**

Description:

RS-485 (bus) touch-operated wall base with three buttons (call, presence and code blue), female DIN-8 connector compatible with LLC-75x call handsets and three reassurance LEDs, one for each button. Easy to clean thanks to the antibacterial coating on its front panel. A call can be initiated using the red call button, presence can be registered using the green button and a code blue can be activated using the button of the same colour. Both the red and blue LEDs indicate the status of the corresponding call. Flush-mounted or surface-mounted installation.

CÓDIGO-CODE-CODE	9410365
MODELO-MODEL-MODÈLE	LLC-903
Conector de pera Hand Set connector Prise manipulateur/poire d'appel	DIN 8
Color de Botón Push button color Boutons couleur	Rojo, Red, Rouge **/** Verde, Green, Vert **/** Azul, Blue, Bleu
Alimentación Power supply Alimentation	24V
Consumo (stand by) Energy consumption (stand by) Consommation (stand by)	10 mA
Consumo (max.) Energy consumption (max.) Consommation (max.)	40 mA
Dimesiones Size Dimensions	80x80x10mm
Peso Weight Poids	O,08Kg
Material Material Matériel	ABS/Polycarbonate
Color Color Couleur	Blanco, White, Blanc (RAL 9001)
Temperatura operacional Operating temperature Température de fonctionnement	-10°C to 55°C
Indice de protección Protection Indice de Protection	IP 42
Instalación Mounting Installation	Empotrado, Embedded, Encastré (ACC-100 / ACC-101) En superficie, On surface, En saillie (ACC-110)
Normativa (seguridad) Normative (security) Norme (sécurité)	EN 60950-1:2006
Normativa (emisiones electromagneticas) Normative (electromagnetic emissions) Norme (champs magnétique)	EN 61000-3-3
Conector de red Net Connector Connexion	RJ-45