

943 NETWORK COMPONENTS

INDOOR ACCESS POINT (AP)



Code : **9430107**

Model : **WFI-200**

CÓDIGO-CODE-CODE	9430107
MODELO-MODEL-MODELE	WFI-200

Wireless

Standard		IEEE802.11 ac/n/g/b/a
MIMO		MU-MIMO
Wireless speed	2.4 GHz	300Mbps
	5 GHz	866Mbps
Frequency band	2.4 GHz	<ul style="list-style-type: none"> USA (FCC): 2.412 to 2.462 GHz Europe (ETSI): 2.412 to 2.472 GHz
	5 GHz	<ul style="list-style-type: none"> USA (FCC): 5.15 to 5.25 GHz; 5.725 to 5.850 GHz European (ETSI): 5.15 to 5.35 GHz; 5.470 to 5.725 GHz
Bandwidth		20-, 40- and 80-MHz
Conducted typical transmit output power*1 (limited by local regulatory requirements)	US (2.4GHz/5GHz)	23/23dBm
	EU (2.4GHz/5GHz)	19/23dBm

RF Design

Antenna type		2x2 MIMO Embedded Antenna
Antenna gain	2.4 GHz	3 dBi
	5 GHz	4 dBi
Minimum receive sensitivity		up to -99 dBm

WLAN feature

Band Steering		Yes
WDS/ Mesh*2		Yes
Fast roaming		Pre-authentication, PMK caching and 802.11r/k/v
DCS		Yes
Load balancing		Yes

Security

encryption		WEP/ WPA/WPA2-PSK/WPA3
authentication		WPA/WPA2-Enterprise/ EAP/ IEEE 802.1X/ RADIUS authentication
Access management		L2-isolation/ MAC filtering

Networking

IPv6		Yes
VLANs		Yes
WMM		Yes
U-APSD		Yes
DiffServ marking		Yes

*1: Conducted typical transmit output power excludes antenna gain. For total (EIRP) transmit power, add antenna gain.

*2: WDS, ZyMesh, Smart Mesh and Industry's Open Mesh, Easy Mesh are different mesh systems that do not work with one another.

CÓDIGO-CODE-CODE	9430107
MODELO-MODEL-MODELE	WFI-200

Management

Operating mode		Cloud managed / standalone
ZON Utility		<ul style="list-style-type: none"> Discovery of Zyxel switches, APs and gateways Centralized and batch configurations <ul style="list-style-type: none"> - IP configuration - IP renew - Device reboot - Device locating Web GUI access Firmware upgrade Password configuration
Zyxel Wireless Optimizer		<ul style="list-style-type: none"> WiFi AP planning WiFi coverage detection Wireless health management
Web UI/ CLI		Yes
SNMP		Yes

Physical Specifications

Item	Dimensions (WxDxH) (mm/in.)	140 x 140 x 37.5 / 5.51 x 5.51 x 1.48
	Weight (kg/lb.)	249/0.55
Packing	Dimensions (WxDxH) (mm/in.)	240 x 155 x 60 / 9.45 x 6.10 x 2.36
	Weight (kg/lb.)	560 / 1.23
Included accessories		<ul style="list-style-type: none"> Power adapter Ceiling-mount plate
MTBF(hr)		630794

Physical Interfaces

Ethernet port		1x 10/100/1000M LAN
Power		<ul style="list-style-type: none"> Input: AC 100 - 240V - 50/60 Hz 0.3A; Output: DC +12V 1A PoE (802.3af); power draw 11 W

Environmental Specifications

Operating	Temperature	0°C to 50°C/32°F to 122°F
	Humidity	10% to 90% (non-condensing)
Storage	Temperature	-40°C to 70°C/-40°F to 158°F
	Humidity	10% to 90% (non-condensing)

Certifications

Radio		FCC Part 15C, FCC Part 15E; ETSI EN 300 328, EN 301 893; LP0002, EN 60601-1-2
EMC		FCC Part 15B, EN 301 489-1; EN 301 489-17, EN55022, EN55024, EN61000-3-2/-3, BSMI CNS13438
Safety		EN 60950-1, IEC 60950-1; BSMI CNS14336-1