

972 VIDEO DOOR ENTRY SYSTEM KITS

ERLEA PLUS H-FREE 7INCH.KIT.1 BUTTON

Code : **9720165**

Model : **KVS-31221**

Description

2-Wire video door entry system kit for villa. Entrance panel with a touch call button, rainshield, camera with 120° wide view and proximity key reader. This video entry system gives you full control over the access of visitors to your property and, in addition, it allows you to identify the person who calls. The automatic switch-on system makes it possible to see the image captured by the entrance panel camera without having first to receive a call. The automatic switch-on function is useful in situations of surveillance or when you wish to communicate with the entrance panel for whatever reason. As an additional feature, the monitor keeps an automatic visual record of visitors whose calls are unanswered. When a call is not answered, the monitor automatically saves an image of the person making the call. This Kit includes a DIN rail power supply.



CÓDIGO-CODE-CODE		9720165
MODELO-MODEL-MODÈLE		KVS-31221
ALIMENTADOR - POWER SUPPLY UNIT - ALIMENTATION		
ALIMENTACIÓN DE RED MAINS SUPPLY ALIMENTATION DE RÉSEAU		100-240 V~ <small>50/60Hz</small>
		0.3 A (máx.)
SALIDAS OUTPUTS SORTIES		15 V _{DC}
		1 A (máx.)
TEMPERATURA DE FUNCIONAMIENTO OPERATING TEMPERATURE TEMPÉRATURE DE TRAVAIL		-10.. +50 °C
MONITOR - MONITOR - MONITEUR		
PANTALLA SCREEN ÉCRAN		7" COLOR TFT LCD 7" COLOR TFT LCD 7" COULEUR TFT LCD
ALIMENTACIÓN INPUT POWER ALIMENTATION		DC15V/1A
TONOS DE LLAMADA RINGTONE SONNERIES		6 Melodías 6 Ringtones 6 Sonneries
INSTALACIÓN INSTALLATION INSTALLATION		De superficie Surface mount Saillie
TEMPERATURA DE FUNCIONAMIENTO OPERATING TEMPERATURE TEMPÉRATURE DE TRAVAIL		5.. +55 °C
PLACA DE CALLE - ENTRANCE PANEL - PLATINE DE RUE		
CÁMARA VIDEO UNIT CAMÉRA		1/3" Color CCD 1/3" Color CCD 1/3" Couleur CCD
CONEXIÓN CONNECTION CONNEXION		2 Hilos 2 Wire 2 fils
TIEMPO PARA CONTESTAR TIME TO ANSWER TEMPS DE RÉPONSE À L'APPEL		90 Seg 90 Sec 90 Sec
TIEMPO DE CONVERSACIÓN TIME FOR CONVERSATION TEMPS DE CONVERSATION		120 Seg 120 Sec 120 Sec
ABREPUERTAS ELECTRIC LOCK GÂCHE		15Vdc: ≤500mA
INSTALACIÓN INSTALLATION INSTALLATION		De superficie Surface mount Saillie
PROTECCIÓN IP IP PROTECTION PROTECTION IP		IP55
TEMPERATURA DE FUNCIONAMIENTO OPERATING TEMPERATURE TEMPÉRATURE DE TRAVAIL		-10.. +50 °C