# TOP MODULAR ENTRANCE PANELS

## MOD.MAN-420 ACTI.VIEW.CAM.CARD H IACCESS



#### Code : **9670195**

#### Model : MDT-422

#### Description

Upper module to be used in push-buttons L201 entrance panels. Triple module, the GRF-302 audio unit, the TCB-075 video unit, the RVE-024 loudspeaker and microphone module and card holder are included.

### 9640021 TCB-075 Description

Color camera module to be mounted in L201 entrance panel. This module is the element in charge of capturing the image of the person making the call. It has white LEDs for night lighting. With ACTIVE VIEW Technology, Colours as you had never seen before. Our camera offers astonishing quality, even in backlight conditions, glare and sudden changes in brightness thanks to its WDR function. To be used in 2-wire video door entry systems

#### **Entrance** Panel

Available in modular format, with upper and lower modules. The upper module can be simple, double or triple. The lower module is available with simple or double push-buttons.

| CÓDIGO-CODE-CODE                                  |   | 9640021                                     |
|---|---|---|
| MODELO-MODEL-MODÈLE                               |   | TCB-075                                     |
| SENSOR<br>SENSOR<br>CAPTEUR                       |   | 1/3" WDR CMOS ACTIVE VIEW                   |
| ILUMINACIÓN<br>LIGHTING<br>ILLUMINATION           |   | Leds blancos<br>White leds<br>leds blanches |
| ÁNGULO DE VISIÓN<br>VIEW ANGLE<br>ANGLE DE VISION | Н | 70°   |
|   | V | 65°   |
| ORIENTACIÓN<br>ORIENTATION<br>ORIENTATION         |   | + 10°→<br>↓                                 |
| PLACA DE CALLE<br>PLAQUE DE RUE<br>ENTRANCE PANEL |   | Línea 201<br>L201<br>201 Line               |



| CÓDIGO-CODE-CODE           | 9610044                            |
|----------------------------|------------------------------------|
| MODELO-MODEL-MODÈLE        | GRF-302                            |
| Regulación de volumen:     | En ambos sentidos                  |
| Sistema:                   | 2 HILOS                            |
| Alimentación del sistema:  | 18Vdc                              |
| Tensión de funcionamiento: | 12,5Vdc – 18Vdc (en BUS B2, B3)    |
| Abrepuertas compatible:    | 12Vdc – 18Vdc máx. 500mA (≥40 Ohm) |
| Medidas del equipo:        | 90mm x 106mm x 26mm                |
| Placa de calle:            | iBLACK ó L201                      |