

940 CONTROLLERS

EMERGENCY CALL POINT IP SURFACE CAMERA



Code : **9400326**

Model : **CIC-615**

Description:

The ALCAD video intercom allows fast and easy emergency calls, thus guaranteeing a quick and effective response from the staff.

On the front we find a fisheye camera operating 24/7 which gives to the staff a complete view of everything that happens on the front of the terminal and on both sides thanks to the wide angle of the camera.

This visual capacity will not be diminished at night because of infrared qualities, so in zero light conditions the camera will continue working.

To establish the call, under the camera we find a large red button and once it is pressed it will initiate the audio call.

Once the call is accepted by the staff, the high-definition IP voice communication is established and it will allow communication thanks to the powerful loudspeaker and adjustable microphone.

In addition, if necessary, pre-recorded voice audios can be played at the designated terminals. In this way, in the event of fire or an attack, the appropriate warnings and indications may be issued in each case, facilitating appropriate actions by the students.

The voice communication center is made of steel, which gives it anti-vandalism qualities, ensuring its durability against external aggressions and the passage of time.

General characteristics

- 5Mpx fisheye camera with 24/7 operation
- IR vision
- SIP voice communication
- Pre-recorded audio broadcasts

Applications

- Continuous visual control of the surrounding area.
- Reception of emergency calls.
- Assistance through voice communication.
- Issuance of emergency notices.

CÓDIGO / CODE	9400326
MODELO / MODEL	CIC-615
Boton / Push button	Botón rojo de llamada / Red push button for call
Cámara /Camera	5MP / lens of 1.1mm ,Angle of view: 360°
Iluminación mínima / Min. Illumination	Color 0.1lux@ F1.2(AGC ON) B/W 0 lux @IR ON
IR alcance / Range	5m
Atlavoz / Speaker	8 ohm, 05W
Audio Codec	SIPv2, G711
Material	Acero/steel/ABS
Color / Colour	Acero/steel
Temperatura/Operating temperature	5°C - 55°C
Conector de red / Net connector	Ethernet (RJ45)