963 DOOR ENTRY SYSTEM MONITORS

KABI 10" IPAL MONITOR WHITE WIFI

Code : **9630078**

Model : **MVC-250**

Do not be fooled by the size of the KABI 10 "touch monitors. Our home terminals are the heart of the entire IPAL system and allow you to take advantage of all its possibilities: one device is responsible for reception and / or recording calls from the entrance panel, and at the same time controls the integration of digital home devices or IP security cameras.

To offer an even more real experience, our monitors allow you to customize the control screens in rooms where digital home devices are connected.

Take a photo of the desired room, upload it to the monitor and assign it the necessary icons. And that's it!

CODE	9630078	
MODEL	**MVC-250**	
Operating system		Android
Front • Communication • Screen • Push buttons • Camera		• Hands free • 10 inches capacitive touch screen • Mechanical side buttons for shortcuts • Integrated front camera for two-way video calls
Video door entry system functions • Unanswered calls • WiFi • Two-way video call • Remote funtions • "Don't disturb" function • "Landing call" function • Ring tones • Other functions		• Yes • Yes • Video call with concierge and / or apartments (authorized video image with a button by the user during the call) • From the mobile phone with the "IPAL by ALCAD" app: Receiving audio and video calls, remote door opening, monitoring, presence simulation, etc • Yes, Scheduled • Yes • Customizable via SD card • Direct call to concierge and / or apartments. Adjust screen brightness and ringing and voice volume from the menu
Home automation • Conectivity • Control RF accessories • Security RF accessories • Wired alarms • Scenes		• Wireless (RF 868MHz), WiFi and Wired Alarms • Lighting, blinds, curtains, plugs, heating • Gas, flood, smoke, movement, Door / window • 4 independent NO or NC circuits (with MCO-300 accessory not included) • Scene settings (out of home, at home, sleep, etc.) integrated and customizable by the user
Video compression		H.264
Protocol		TCP/IP
Power supply		PoE (also allows 12Vdc power)
Consumption	W	5W (at rest); 6,5W (Working)
Mounting		With flush-mounted box (CME-020 not included)
Working temperature	°C	-10°C ... +55°C
Dimensions		285 x 158 x 15mm (width x height x depth)
Packing weight	Kg	0,73 Kg
Packing dimensions	mm	302 x 192 x 42 mm (width x height x depth)