

971 MODULAR ENTRANCE PANELS

AUDIO & VIDEO MODULE 2 BUTTONS USOA



Code : **9710013**

Model : **MVG-021**

Description

Complete module for USOA entrance panel. 2 windows. It includes EVG-021 electronic module and CVG-021 front glass

The luminous accessibility icons offer visual information of the operating states of the panel (calling, conversation, door open and system busy), complying with the SUA-9 accessibility regulations of the Technical Building Code and following the recommendations of the ONCE (National organization of the spanish blinds).

9770085 EVG-021 Description

Electronic module for USOA entrance panel. Category: Spare parts.

It includes the audio unit, voice synthesizer (14 languages), a wide-angle Active View camera, a handicap display. This module incorporates 2 tactile call buttons arranged in 2 columns (Left and right).

9770100 CVG-021 Description

Frontal glass for USOA entrance panel. Category: Spare parts. Front belonging to the complete module MVG-021

USOA is the Alcad entrance panel with a continuous profile and modular composition. It consists of frames of different sizes and with different numbers of windows where the different modules are fitted: as main audio or video module, push-button modules, iaccess module, card holders ... etc. There are two module sizes: P and G. The G modules occupy 2 frame windows, and the P modules occupy a single window.

Its modularity allows total freedom of choice for the creation of compositions and, at the same time, facilitates the integration of all technologies in the same equipment and with the same aesthetics.

| Code | | 9710011 | 9710012 | 9710013 |
|---|----|--|-----------|------------------------|
| Model | | MVG-011 | MVG-000 | MVG-021 |
| Conection | | 2 Wire | | |
| Number of windows | | 2 | | |
| Front <ul style="list-style-type: none"> • Materials • Color • Thickness | mm | <ul style="list-style-type: none"> • Tempered glass <ul style="list-style-type: none"> • White • 3mm | | |
| Number of tactile buttons | | 1 Button (Right) | No Button | 2 Buttons (Left/Right) |
| Camera <ul style="list-style-type: none"> • Sensor • Lighting • View angle | | <ul style="list-style-type: none"> • 1/3" WDR CMOS ACTIVE VIEW <ul style="list-style-type: none"> • White Leds • D: 170° | | |
| Power supply | | DC 12.5-18V | | |
| "Door Opened" Message | | 14 Selectable languages | | |
| Accessibility Indicator <ul style="list-style-type: none"> • Complying with regulations | | 4 Light indicators SUA-9 (CTE) | | |
| Working temperature | °C | -10°C ,, +55°C | | |
| Packing weight | Kg | 0.32 | 0.31 | 0.32 |
| Packing dimensions | mm | 115 x 105 x 65 mm | | |