

971 MODULAR ENTRANCE PANELS

AUDIO MODULE 2 BUTTONS USOA



Code : **9710016**

Model : **MAG-021**

Description

Complete module for USOA entrance panel. 2 windows. It includes EAG-021 electronic module and CAG-021 front glass

The luminous accessibility icons offer visual information of the operating states of the panel (calling, conversation, door open and system busy), complying with the SUA-9 accessibility regulations of the Technical Building Code and following the recommendations of the ONCE (National organization of the spanish blinds).

9770088 EAG-021 Description

Electronic module for USOA entrance panel. Category: Spare parts.

It includes the audio unit, voice synthesizer (14 languages), a handicap display. This module incorporates 2 tactile call buttons arranged in 2 columns (Left and right).

9770103 CAG-021 Description

Frontal glass for USOA entrance panel. Category: Spare parts. Front belonging to the complete module MAG-021

USOA is the Alcad entrance panel with a continuous profile and modular composition. It consists of frames of different sizes and with different numbers of windows where the different modules are fitted: as main audio or video module, push-button modules, iaccess module, card holders ... etc. There are two module sizes: P and G. The G modules occupy 2 frame windows, and the P modules occupy a single window.

Its modularity allows total freedom of choice for the creation of compositions and, at the same time, facilitates the integration of all technologies in the same equipment and with the same aesthetics.

Code		9710014	9710015	9710016
Model		MAG-011	MAG-000	MAG-021
Conection		2 Wire		
Number of windows		2		
Front <ul style="list-style-type: none"> • Materials • Color • Thickness 	mm	<ul style="list-style-type: none"> • Tempered glass <ul style="list-style-type: none"> • White • 3mm 		
Number of tactile buttons		1 Button (Right)	No Button	2 Buttons (Left/Right)
Power supply		DC 12.5-18V		
"Door Opened" Message		14 Selectable languages		
Accessibility Indicator <ul style="list-style-type: none"> • Complying with regulations 		4 Light indicators SUA-9 (CTE)		
Working temperature	°C	-10°C ... +55°C		
Packing weight	Kg	0.31	0.30	0.31
Packing dimensions	mm	115 x 105 x 65 mm		