

973 ACCESSORIES

IPAL SYSTEM 24 PORTS SWITCH

Code : **9730099**

Model : **DIV-324**

Description

Accessory for Door Entry Systems installations. Derivator Switch IP system.
24 PoE bypass outputs. 1 input and 24 pass-through output.



Code	9730099
Model	DIV-324
Network Port	24 port 10/100/1000M PoE RJ45 port (Adaptive MDI/MDIX)
	4 Gigabit SFP port
Forwarding rate	Gigabit line speed forward
Transmission speed	10BASE-Tor 100BASE-TX, 1000BASE-TX, 1000BASE-X
Network protocols and standards compliant	IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3ab 1000BASE-TX
	IEEE 802.3x Flow Control
	IEEE 802.3af/at Power over Ethernet
Network protocol and standard	Bandwidth: 56Gbps (non-blocking)
	Network delay (100 to 100M bps) : maximum 20 μs(using 64 byte packet)
	Network delay (100 Mbps ~ 100 Mbps) : maximum 10μs(using 64 byte packet)
	Frame filtering and transmission rate: •10M : 14,800pps , •100M : 148,809pps , •1000M: 148,8019pps
LEDs indicator	Power
	LINK/ACT, POE
POE pin	1/2(+), 3/6(-)
Power supply support	PoE power: 400W;single port max 30W
	Total power: Maximal 400W; 110~240VAC/48VDC /8.3A power output; (Each country use customized power plug)
	Mainboard power supply: 12VDC/1A
Dimensions	(LxWxH): 440mm x 290mm x 44 mm
	Weight: 5.5kg
Environment	Operating Temperature: 0°~40°C
	Operating Humidity: 10%~ 90% (Non-condensing)
EMC	· CE Class B
	· FCC Part 15, Class B
	· VCCI Class B
	· C-Tick
Certifications	CE/ROHS/FCC
Warranty	1 year