

972 VIDEO DOOR ENTRY SYSTEM KITS

ENARA 4.3" KIT 1 BUT ACTIVE VIEW USOA

Code : **9720169**

Model : **KVS-55121**



ALCAD video door entry system kits Include all the necessary material to carry out the installation, with the exception of the cable. Include entrance panel for the building with video camera, power supply and indoor monitor. The installation can be completed with accessories, such as rainshields or decorative frames, and with different extensions, such as second entrance panel or monitors and additional telephones.

Code		9720169
Model		KVS-55121
Conection		2 Wire
Imput Voltage		Through the 2-wires BUS (12,5 ... 18Vdc)
ENTRANCE PANEL		
Number of windows		2
Front <ul style="list-style-type: none"> • Materials • Color • Thickness 	mm	<ul style="list-style-type: none"> • Tempered glass <ul style="list-style-type: none"> • White • 3mm
Number of tactile buttons		1 Button (Right)
Camera <ul style="list-style-type: none"> • Sensor • Lighting • View angle 		<ul style="list-style-type: none"> • 1/3" WDR CMOS ACTIVE VIEW <ul style="list-style-type: none"> • White Leds • D: 170°
"Door Opened" Message		14 Selectable languages
Accessibility Indicator <ul style="list-style-type: none"> • Complying with regulations 		4 Light indicators SUA-9 (CTE)
Working temperature	°C	-10°C ,, +55°C
Packing weight	Kg	0.32
Packing dimensions	mm	115 x 105 x 65 mm
ENARA MONITOR		
Screen		TFT Colour 4,3"
On-screen menu		Yes
Communication		Free hands
call volume regulation		"Do not disturb"; 0-8
Buttons for auxiliary functions		1
Capture Photo/Video		Yes/Yes
WiFi		No
Consumption (mA)		40 mA (rest); 375 mA (active)
Work temperature		+5... +55 °C
Connetions		Pluggable terminals
Integrated load and bypass		Yes, configurable by micro-switches
Installation		Surface mount
Proportions		120mm X 168mm X 26mm