

# 943 NETWORK COMPONENTS

---

## CAMERA AI DOME POE IP66



Code : **9430123**

Model : **CMA-100**

Description:

ALCAD's facial recognition solution for real-time people location offers high accuracy thanks to its advanced technology of artificial intelligence, face comparison, smart search, face image search and face database management.

With this, you not only get a real-time location system, but you also get a non-intrusive wandering system that prevents patients from escaping from the facilities.

<b>CÓDIGO-CODE-CODE</b>	<b>9430123</b>
<b>MODELO-MODEL-MODÈLE</b>	<b>CMA-100</b>
Video Compression	H.265/H.264
Resolution	2MP 1920(H)×1080(V)
Image Sensor	1/2.7" Progressive CMOS
Min. Illumination	Color 0.02lux @ F1.2(AGC ON)
Shutter	1/5 ~ 1/20000s
Slow shutter	Support
Lens	2.7 ~ 13.5 mm
F No.	F1.6±5%
Day & Night	IR cut filter with auto switch
WDR	Digital WDR
Video bit rate	128Kbps ~ 8Mbps
Dual Stream	Main, Moblie
Frame Rate	Mainstream(1-30fps optional) 1080P(1920x1080), 960P(1280x960), 720P(1280x720) Substeam VGA(640x480), QVGA (320x240)
Image Settings:	Rotate mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
Privacy Mask	Support
Protocols	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,PPPoE, SMTP,NTP,UPnP,SNMP,HTTPS,FTP,
System Compatibility	ONVIF( Profile S, Profile G)
Interface	RJ45 10M / 100M Ethernet interface x1
Led &IR Range	40 pcs Up to 40m
Video Output:	no
Water Proof	IP 66
Power Supply	DC 12V/POE
Consumption	≤6W
Storage Temperature	-30~+60°C
Operating Temperature	-30~+55°C