

904 BROADBAND AMPLIFIERS

AMPLIFIER UHF-UHF-BIII/DAB LTE700



Code : **9049903**

Model : **CA-460**

Description

Broadband head-end amplifiers with three inputs. Built on a compact chassis, they are capable of supplying a signal to a large number of outlets.

Applications

Designed for analogue and digital terrestrial TV installations in medium-sized MATV networks or individual installations. They are used as the head-end amplifier of the installation.

Characteristics

Made from ABS plastic, with an internal zamak chassis of which provides maximum shielding. F type connectors which affords a connection with minimum mismatching and high shielding. Power supply unit insulated from the rest of the high frequency circuit, complying with all safety standards.

CÓDIGO-CODE-CODE		9049903		
MODELO-MODEL-MODELE		CA-460		
Número de entradas Number of inputs Numero ingressi		3		
Rango de frecuencia Frequency range Range di frequenza	Band	BIII/DAB	UHF1	UHF2
	MHz	160-260	470-694	470-694
Ganancia Gain Guadagno	dB ±TOL	35±1,5		
Regulación de ganancia Adjustable gain range Rango di guadagno regolabile	dB	20	16	
Nivel de salida Output level Livello di uscita	dB μ V	114 (DIN45004B) 111 (IMD3 -66dB) AM-TV 123,5 (IMD3 -35dB) DVB-T 104 (IMD2 -60dB)		
Figura de ruido Noise figure Figura di rumore	dB ±TOL	4±1,5	8±1,5	
Pérdidas de retorno Return losses Perdite di ritorno	dB	≥10		
Tensión de salida Output voltage Tensione di uscita	Vdc	12		
	mA	50 _{AUTO}		
Tensión de red Mains voltage Tensione di rete	Vac	230±15% 50/60Hz		
	W	4		
Temperatura de funcionamiento Operating temperature Temperatura di funzionamento	°C	-10.. +65		
Índice de protección Protection index Indice di protezione		IP20		