

# 980

# **COMPLETE MODULES**

## ALOI AUDIO & VIDEO PANEL 1 BUTTON



Code: 9800227

Model: PTS-63201

### Description

Vandal resist entrance panel for 2-wire video intercom installations. It includes the EVG-000 main module, the same one used by the USOA entrance panel. This panel has 1 call push-button.

#### Entrance panel

- Construction in stainless steel AISI316L 2,5 mm thickness, with special vandal proof screws.
- 100% flat surface, without protrusions.
- Card holders, and camera and handicap icons front screens of 6mm thickness.
- Protection against impacts up to rate: IK09.
- IP55 protection from dust and low-pressure water jets from any direction.
- Attractive, professional and "Made in Spain" finishing.
- Handicap module with voice synthesizer with 14 selectable languages for "open door" message. It includes the possibility of mute mode.
- iACCESS optional. Comfort and distinction for owners and tenants.
- Automatic lighting of card holders in dark conditions (with LDR sensor)
- Camera with demisting system, which is activated automatically thanks to its humidity and temperature sensors.
- Greater audio power thanks to its two speakers.



CODE		9800227
MODEL		PTS-63201
Dimensions	mm	145 x 212
Material • Thickness	mm	AISI 316L 2,5
Compatible flush box • Dimensions	mm	9740244 CMO-602 125 x 195 x 50
Number of pushbuttons		1
Pushbutton Rows		1
Protection against impact rate	IK	IK09
Camera • Sensor • Lighting • View angle		1/3" WDR CMOS ACTIVE VIEW White LED D:170° (Wide angle)
"Door Opened" Message		14 Selectable languages
Accessibility Indicator • Complying with regulations		4 Luminous Icons SUA-9 (CTE)
iACCESS		Optional
Packing weight	Kg	1,18
Packing dimensions	mm	170 x 340 x 80