

980 COMPLETE MODULES

ALOI AUDIO&VIDEO PANEL 9 SIMPLE BUTTONS



Code : **9800235**

Model : **PTS-63209**

Description

Vandal resist entrance panel for 2-wire video intercom installations. It includes the EVG-000 main module, the same one used by the USOA entrance panel. This panel has 9 call push-buttons arranged in 1 column.

Entrance panel

- Construction in stainless steel AISI316L 2,5 mm thickness, with special vandal proof screws.
- 100% flat surface, without protrusions.
- Card holders, and camera and handicap icons front screens of 6mm thickness.
- Protection against impacts up to rate: IK09.
- IP55 protection from dust and low-pressure water jets from any direction.
- Attractive, professional and "Made in Spain" finishing.
- Handicap module with voice synthesizer with 14 selectable languages for "open door" message. It includes the possibility of mute mode.
- iACCESS optional. Comfort and distinction for owners and tenants.
- Automatic lighting of card holders in dark conditions (with LDR sensor)
- Camera with demisting system, which is activated automatically thanks to its humidity and temperature sensors.
- Greater audio power thanks to its two speakers.

| CODE | | 9800235 |
|--------------------------------|----|---------------------------|
| MODEL | | PTS-63209 |
| Dimensions | mm | 145 x 404 |
| Material | | AISI 316L |
| • Thickness | mm | 2,5 |
| Compatible flush box | | 9740248 CMO-610 |
| • Dimensions | mm | 125 x 387 x 50 |
| Number of pushbuttons | | 9 |
| Pushbutton Rows | | 9 |
| Protection against impact rate | IK | IK09 |
| Camera | | |
| • Sensor | | 1/3" WDR CMOS ACTIVE VIEW |
| • Lighting | | White LED |
| • View angle | | D:170° (Wide angle) |
| "Door Opened" Message | | 14 Selectable languages |
| Accessibility Indicator | | 4 Luminous Icons |
| • Complying with regulations | | SUA-9 (CTE) |
| iACCESS | | Optional |
| Packing weight | Kg | 2,06 |
| Packing dimensions | mm | 170 x 485 x 80 |