

# 972 VIDEO DOOR ENTRY SYSTEM KITS

ERLEA H-FREE 7INCH.KIT.1 BUT.2-W.PHOTO

Code : **9720156**

Model : **KVS-31121**



## Description

2-Wire video door entry system kit for villa. This video entry system gives you full control over the access of visitors to your property and, in addition, it allows you to identify the person who calls. The automatic switch-on system makes it possible to see the image captured by the entrance panel camera without having first to receive a call. The automatic switch-on function is useful in situations of surveillance or when you wish to communicate with the entrance panel for whatever reason. As an additional feature, the monitor keeps an automatic visual record of visitors whose calls are unanswered. When a call is not answered, the monitor automatically saves an image of the person making the call. This Kit includes a DIN rail power supply.

## 9720156 KVS-31121

### ENTRANCE PANEL

Specifications		
Color camera	1/3" color CCD; 1.5lux; Angle 62~90°	
Connection	2 wires (non-polarized)	
Power Consumption	≤0.7W (standby) ; ≤6W (working)	
Call Time	90s	
Talk/Monitor Time	60s	
Communication	handsfree	
E-LOCK	Working Voltage: DC12V	
	LOCK RESISTANCE	10Ω~50Ω, Lock maintain current: ≤150mA
Ambient Temperature	-30~+70°C	
Installation	surface mount	
Product Dimensions(WxHxD)	106.9mm × 157mm × 36.3mm	

### MONITOR

Specifications		
Input Voltage	DC18V	
Power Consumption	≤5W(standby) ; ≤15W(working)	
Screen	7" color LCD	
Cable & Cable Length	cable to Outdoor Camera: 2 wires ( non-polarity; 1 mm <sup>2</sup> up to 50 meters)	
Call Time	call from Outdoor Camera: 90s	
Talk/Monitor Time	60s	
Ringtone	9 chord ringtone	
Capacity for snapshots	auto- captured:20 groups(3pcs/group) manual-captured:50 pcs	
Communication	handsfree	
Ambient Temperature	-10~+55°C	
Installation	surface mount	
Dimensions (WxHxD)	208mm × 138mm × 25mm	