

904 BROADBAND AMPLIFIERS

INDOOR AMP 1 OUTPUT CATV RP 30 MHZ



Code : **9040056**

Model : **AI-131**

Description

Broadband apartment amplifier for terrestrial TV, with built-in power supply unit. It amplifies the VHF and UHF bands separately and has an independent gain control for each band. It includes two outputs to make the distribution to two or more televisions. The outputs are equal or unbalanced.

Applications

Designed to enlarge analogue and digital terrestrial TV installations within an apartment or house. It amplifies the TV signal so a distribution with several new outlets can be made from the signal of one TV outlet or from the coaxial cable entering the house. The levels are easily adjusted by means of the two gain controls.

Characteristics

Made from ABS plastic, with an internal zamak chassis which gives maximum shielding. The power supply unit is insulated from the rest of the high frequency circuit, complying with the safety regulations for the installer and the user. Fixed to the wall by means of the supplied screws and wall-plugs. F type connectors.

| CODE | | 9040056 | | 9040057 | |
|-------------------------------|--------|--|--------------------------------|-----------|--------------------------------|
| MODEL | | AI-131 | | AI-133 | |
| Outputs | | 1 | | | |
| Frequency range | Band | RP | VHF/UHF | RP | VHF/UHF |
| | MHz | 5-30 | 47-862 | 5-65 | 86-862 |
| Gain | dB±TOL | -2.5 ±0.5 | 24 ±1.0 OUT 1 10 ±1.0 OUT 2 | -2.5 ±0.5 | 24 ±0.1 OUT 1 10 ±0.1 OUT 2 |
| Flatness response | dB | ±1.2 | ±1.5 | ±0.5 | ±1.5 |
| Gain adjust | dB | - | 13 | - | 13 |
| Adjustable equalization range | dB | - | 20 | - | 18 |
| Output level | dBµV | 113/99 DIN 45004B 110/96 (IMD ₃ -60 dB) 100/85 (IMD ₂ -60 dB) 97/83 (CTB -60 dB) 95/80 (CSO -60 dB) 97/83 (XMOD -60 dB) | | | |
| Return loss | dB | ≥10 | | | |
| Noise figure | dB | 6 ±1.0 | | | |
| Mains voltage | V~ | 230 ±10% ⁽¹⁾ 50/60 Hz | | | |
| | W | 5.5 | | | |
| Operating temperature | °C | -10..+65 | | | |
| Protection index | | IP 20 | | | |
| Units per packing | | 1 | | | |
| Packing weight | Kg | 0.4 | | | |
| Packing dimensions | mm | 115 x 102 x 45 | | | |