

# 905 MODULAR AMPLIFICATION EQUIPMENT

## THREE CHANNEL AMPLIFIER UHF, G=53 DB



Code : **9050024**

Model : **ZG-413**

### Description

Multichannel amplifier for the UHF band designed to work with a group of adjacent channels. Each module permits the amplification and equalisation of two to four channels. The level of the group of channels can be adjusted but not each channel independently. High gain and output level. The initial channel of the group should be specified in the order.

### Applications

Large digital and analogue terrestrial MATV installations where adjacent analogue or digital channels exist. Recommended for use in areas of reception where the relation in levels between analogue and digital channels is constant. Normally used to amplify one analogue channel along with several digital channels.

### Characteristics

Each module consists of a three-stage input filter, an amplifier and an output filter which is three-stage, the filters are cavities. Filters remain highly stable with variations in temperature. Attenuator using an active MOSMIC regulator reduces the noise figure. 30dB multiturn attenuator. Switch to supply power to preamplifiers with protection against short circuits.

CODE		9050023	9050024	9050026	
MODEL		ZG-412	ZG-413	ZG-414	
TV system		AM-TV / DVB-T			
Connection		F female			
Number of channels		2	3	4	
Frequency range	Band	UHF			
	MHz	470-862			
Gain	dB $\pm$ TOL	53 $\pm$ 3.0			
Adjustable gain range	dB	30			
Maximum output level	dB $\mu$ V	2x 123.5 DIN 45004K 2x 109.0 DIN 45004B 2x 106.0 (IMD <sub>3</sub> -66 dB) AM-TV 2x 118.5 (IMD <sub>3</sub> -35 dB) DVB-T			
Selectivity	dB	C <sub>n</sub> - C <sub>n</sub> $\pm$ 2	27	21	18
		C <sub>n</sub> - C <sub>n</sub> $\pm$ 3	43	35	31
		f <sub>c</sub> - f <sub>c</sub> $\pm$ 12MHz	25	19	16
Return loss	dB	$\geq$ 10			
Output voltage	V <sub>DC</sub>	+24			
	mA	33			
Power supply	V <sub>DC</sub>	+24			
	mA	80			
Operating temperature close to equipment	$^{\circ}$ C	-10..+65			
Room temperature with/without fan	$^{\circ}$ C	-10..+55/+45			
Protection index		IP 20			
Units per packing		1	40		
Packing weight	Kg	0.51	21.0		
Packing dimensions	mm	200 x 80 x 40	375 x 375 x 225		