

906 TAP-OFFS AND SPLITTERS

TAP-OFF IF 2 OUT 30 DB EQUALISED

Code : **9060035**

Model : **FD-225**

Description

Equalised tap-offs for terrestrial and satellite TV with two tap outputs which cover the 5 to 2,400 MHz frequencies. They distribute part of the input signal to their tap outputs and the main part of the signal continues to the output. The equalisation of the tap outputs compensates the losses of the coaxial cable. Available in different tap-off attenuation values.



Applications

SMATV installations with a tree-shaped distribution. The tree-shaped distribution reduces the number of distribution elements, and reduces the metres of coaxial cable to be installed, even though the headend to outlet distances remain constant. For installation in buildings with many floors due to the low through loss of the tap-offs.

Characteristics

Voltage blockage in the tap-offs. Shielded zamak chassis and metal plate. Connectors on the lower part to facilitate the connections. Reduced dimensions. Fits in a 100 x100 mm box.

CODE		9060053	9060033	9060034	9060035
MODEL		FD-210	FD-213	FD-219	FD-225
Connection		F female			
Outputs		2			
Frequency range	MHz	5 - 2400			
Tap loss	dB ±1.0	5-47 MHz 26.0-24.5 47-230 MHz 24.5-21.5 470-862 MHz 17.0-13.0 950-2150 MHz 12.5-8.5 2150-2400 MHz 8.5-8.0	28.0 28.0-25.0 21.5-17.5 17.0-12.0 12.0-11.5	32.0 32.0-30.5 27.5-24.0 23.0-17.5 17.5-17.0	36.0 36.0-34.5 33.0-30.0 30.0-26.0 26.0-25.5
Flatness response	dB	±1.0			
Through loss	dB ±0.5	5-47 MHz 0.8 47-230 MHz 0.8-1.0 470-862 MHz 1.2-1.7 950-2150 MHz 1.8-3.0 2150-2400 MHz 3.0-3.5	0.6 0.6-0.7 0.9-1.2 1.2-2.0 2.0-2.3	0.5 0.5 0.5-0.8 0.8-1.4 1.4-1.6	0.5 0.5 0.5-0.6 0.6-1.0 1.2
Directivity	dB	5-47 MHz >0 47-862 MHz >0-6 950-2150 MHz >7 2150-2400 MHz >8	>0 >0-5 >5-8 >8	>0 >0-5 >5-7 >7	>0 >0-4 >4-7 >8
Isolation	dB	5-47 MHz >45 47-862 MHz >32 950-2150 MHz >28 2150-2400 MHz >26	>50 >40 >30 >28	>60 >55 >45 >38	>60 >60 >45 >40
Return loss	dB	5-47 MHz >18 47-862 MHz >18 950-2150 MHz >13 2150-2400 MHz >13	>17 >15 >15 >13	>18 >18 >15 >13	
Units per packing		6			
Packing weight	Kg	0.45			
Packing dimensions	mm	155 x 95 x 40			