

# 907

## OUTLETS AND USER ACCES POINTS

### IF TERMINAL OUTLET, 2 DB, 3 CONNECTORS



Code: 9070086

Model : **BS-102** 

#### Description

Outlets for terrestrial and satellite TV with three male IEC connectors, an IEC female connector and an F-type female connector. They cover frequencies up to 2,300MHz. They allow a feed path via the female F-type connector to the input.

#### **Applications**

Outlets for terrestrial and satellite TV with three male IEC connectors, an IEC female connector and an F-type female connector. They cover frequencies up to 2,300MHz. They allow a feed path via the female F-type connector to the input.

#### Characteristics

Shielded zamak and metal plate chassis. Connection of the coaxial cable by means of screw terminal. Includes TV/R/SAT frontplate, surface box and screws for fixing to a wall.



| CODE               |      |                       | 9070086                     |
|--------------------|------|-----------------------|-----------------------------|
| MODEL              |      |                       | BS-102                      |
| Installation       |      |                       | Final                       |
| Connection         |      |                       | Terminal and clamp          |
| Output connectors  |      | C1                    | IEC male Ø9.52 mm           |
|                    |      | C2                    | IEC female Ø9.52 mm         |
|                    |      | C3                    | F female                    |
| Frequency range    |      | ı                     | 5 - 2,500                   |
|                    | MHz  | C1                    | 5 - 68/125-862              |
|                    | MHZ  | C2                    | 87.5 - 108                  |
|                    |      | C3                    | 950 - 2,500                 |
| Basic loss         | dB   | FM<br>TV<br>SAT       | 2<br>2.7<br>2.3             |
| Isolation 2        | dB   | FM<br>TV<br>SAT       | >24. 3<br>>15<br>>15        |
| Selectivity 3 4 5  | dB   | FM<br>TV<br>SAT       | >15<br>>15<br>>15           |
| Return loss        | dB   | VR<br>FM<br>TV<br>SAT | >7.6<br>>10<br>>7.6<br>>8.2 |
| DC path            | V=   |                       | 34 max                      |
|                    | mA   |                       | 500 max                     |
|                    | Tone |                       | 22 KHz / DiSEqC             |
| Units per packing  |      |                       | 1                           |
| Packing weight     | Kg   |                       | 0.10                        |
| Packing dimensions | mm   |                       | -                           |