

# 907 OUTLETS AND USER ACCES POINTS

## IF TERMINAL OUTLET, 2 DB, 3 CONNECTORS



Code : **9070086**

Model : **BS-102**

### Description

Outlets for terrestrial and satellite TV with three male IEC connectors, an IEC female connector and an F-type female connector. They cover frequencies up to 2,300MHz. They allow a feed path via the female F-type connector to the input.

### Applications

Outlets for terrestrial and satellite TV with three male IEC connectors, an IEC female connector and an F-type female connector. They cover frequencies up to 2,300MHz. They allow a feed path via the female F-type connector to the input.

### Characteristics

Shielded zamak and metal plate chassis. Connection of the coaxial cable by means of screw terminal. Includes TV/R/SAT frontplate, surface box and screws for fixing to a wall.

CODE		9070086	
MODEL		BS-102	
Installation			Final
Connection			Terminal and clamp
Output connectors		C1	IEC male Ø9.52 mm
		C2	IEC female Ø9.52 mm
		C3	F female
Frequency range	MHz	I	5 - 2,500
		C1	5 - 68/125-862
		C2	87.5 - 108
		C3	950 - 2,500
Basic loss ①	dB	FM	2
		TV	2.7
		SAT	2.3
Isolation ②	dB	FM	>24.3
		TV	>15
		SAT	>15
Selectivity ③ ④ ⑤	dB	FM	>15
		TV	>15
		SAT	>15
Return loss	dB	VR	>7.6
		FM	>10
		TV	>7.6
		SAT	>8.2
DC path	V=		34 max
	mA		500 max
	Tone		22 KHz / DiSEqC
Units per packing			1
Packing weight	Kg		0.10
Packing dimensions	mm		-