

941

SENSORES Y ACTUADORES

PULSADOR LLAMADA (V)

Código : **9410225**

Modelo : **LLC-560**

Description

Patient handset with JACK 3,5mm socket for connecting to LLC- 50x call unit. It allows starting a patient call by pressing call push-button. Once a patient call has been started the green LED indicator stands steady ON until the call is cancelled by a nurse presence in the room. Easy to clean antimicrobial cover. Flush mounting.

SPECIFICATIONS	LLC-560	LLC-562
Socket (patient handset connector)	Female JACK 3,5mm	
Patient call button	Text: CALL	
	Icon: Nurse	
	Colour: Green (RAL 601 18, yellow green)	
	Text / Icon colour: Black (RAL 9004, signal black)	
	Indicator led: Green	
Power supply	24 V	
Consumption (idle)	5 mA	
Consumption (maximum)	20 mA	
Dimensions (width x height x deep)	LLC-501 (vertical): 75x120x15 mm LLC-504 (horizontal): 120x75x15 mm	
Plastic	ABS / Polycarbonate	
Colour (plastic)	White (RAL 9003, signal white)	
Operating Temperature	5°C to 55°C	
Protection index	IP 42	
Mounting	Flush mounting (standard box)	
Safety	EN 60950-1:2006	
EMC	EN 61000-3-3	