

943 CODEUR IP / EMETTEUR UHF PAGER

Code : **9430089**

Modèle : **PAG-010**



Description

Le PAG-010 est un émetteur radio VHF / UHF et un codeur pour les messages de radiomessagerie, qui est connecté via IP au système ALCAD NURSE CALL. Il permet d'envoyer des messages d'appels de la salle au personnel soignant, ou des messages d'alarmes techniques au personnel de maintenance. Sa portée peut atteindre jusqu'à 2Km en utilisant une antenne supplémentaire PAG-011.

SPECIFICATIONS - PAG-010

Frequency Range	VHF - 148 - 174 MHz UHF - 440 - 470 MHz
Power Output Available in	5, 25, 50, 100 and 200 Watt
Output Protocols	POCSAG 512, 1200 or 2400bps
Input Protocols	TAP (PET, IXO), COMP1, COMP2, Scope, TEKK, Terminal
Ethernet Port	IEEE 802.3, 10 Base-T, RJ45
Serial Port	RS232C, RJ45, 300 - 57600 Baud (defaults 9600 bps)
External LED Indicators	Power, Busy, PTT, Data, RS232 Tx, RS232 Rx, IP Link, IP Activity
External Connectors	POCSAG: RJ45f With Selectable RS232/TTL
Level Power:	IEC Mains Socket (Rack Only)
Antenna:	N-Type Female 50 Ω
Programming	Via Terminal or Internet Browser
Pager Database	1000 Pagers
Dimensions	Standard 19" Rack Case 439 x 205 x 44 mm
Weight	2.7kg
Power Requirements	110 - 240V AC 50/60Hz (Autosensing) 25w
Operating Temperature	0 °C to 50 °C (20-90% RH Non-Condensing)
Storage Temperature	10 °C - 60 °C (10-95% RH Non-Condensing)
Approvals	FCC, CE, C-tick, ROHS, IC, EN60950