

943 SERVEUR HAUTE DISPONIBILITE



Code : **9430106**

Modèle : **SRG-410**

Description

L'unité SRG-410 centralise toute la gestion des services du système ACCURO, LIVERO et IPTV via un serveur de grande capacité.

Le serveur offre une gestion et une configuration étendues pour répondre à vos besoins, tout en permettant l'intégration avec des logiciels tiers.

Le SRG-410 offre la polyvalence et la flexibilité nécessaires pour alimenter une variété d'applications. Le serveur offre les fonctionnalités suivantes.

- Faites évoluer les ressources de calcul avec les processeurs Intel® Xeon® Scalable de 2e génération et adaptez les performances en fonction de vos exigences de charge de travail uniques.
- Performances optimisées de l'application avec le réglage d'un bouton.
- Stockage flexible avec jusqu'à 14 disques 3,5".
- Stockage de démarrage optimisé m.2 ssds.
- Pour ACCURO et LIVERO, il offre la capacité de gestion de 1 à 1200 centrales.
- Pour IPTV il offre la capacité de gestion de 1 à 2000 STB sans Vod et 1-2000 avec Vod.
- Possibilité de redondance avec un autre SRG-410.

Code	9430106
Model	SRG-410
Form factor	2U rack server
Dimensions and weight	H: 86.80 mm (3.4 in) W: 434 mm (17.1 in) without ears D: 646 mm (25.4 in) with bezel, 648 mm (25.5 in) without bezel Minimum weight: 14.2 kg (31.2 lb) Maximum weight: 28.2 kg (62 lb)
Processor	Intel® Xeon® processor E5-2600 v4 product family Processor sockets: 2 Chipset: C610 Internal interconnect: up to 9.6GT/s; Cache: 2.5MB per core; core options: 4, 6, 8, 10, 12, 14, 16, 18
Memory	DDR4 DIMMs at up to 2400MT/s; 12 DIMM slots: 4GB/8GB/16GB/32GB
I/O slots	Support for up to 5 x PCIe <ul style="list-style-type: none"> • 3 x PCIe 3.0 • 2 x PCIe 2.0
Storage	Up to 8 x 3.5" SAS, SATA, nearline SAS, SSD drives
RAID controllers	Internal controllers: PERC S130 (SW RAID), PERC H330, PERC H730, PERC H730P External HBAs (RAID): PERC H830 External HBAs (non-RAID): 12Gbps SAS HBA
Communications	4 x 1GbE LOM Click here for R530 supported network interface cards (NICs) and host bus adapters (HBAs) and scroll to "Additional Network Cards" section
Power supplies	495W, 750W, 1100W hot-plug PSU; -48V DC 1100W hot-plug PSU; 450W cabled PSU

Code	9430106
Model	SRG-410
Systems management	<p>Systems management: IPMI 2.0 compliant; Dell OpenManage Essentials; Dell OpenManage Mobile; Dell OpenManage Power Center</p> <p>Remote management: iDRAC8 with Lifecycle Controller; iDRAC8 Express (default); iDRAC8 Enterprise (upgrade); 8GB vFlash media (upgrade); 16GB vFlash media (upgrade)</p> <p>Dell OpenManage Integrations:</p> <ul style="list-style-type: none"> • Dell OpenManage Integration Suite for Microsoft® System Center • Dell OpenManage Integration for VMware® vCenter™ <p>Dell OpenManage Connections:</p> <ul style="list-style-type: none"> • HP Operations Manager, IBM Tivoli® Netcool® and CA Network and Systems Management • Dell OpenManage Plug-in for Oracle® Database Manager
Optional supported hypervisors	Citrix® XenServer, VMware vSphere® ESXi®, Red Hat® Enterprise Virtualization
Operating systems	<p>Microsoft Windows Server® 2008 R2 Microsoft Windows Server 2012 Microsoft Windows Server 2012 R2 Novell® SUSE® Linux Enterprise Server Red Hat Enterprise Linux</p>
Rack support	ReadyRails™ II sliding rails for tool-less mounting in 4-post racks with square or un-threaded round holes or tooled mounting in 4-post threaded hole racks, with support for optional tool-less cable management arm
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you