942 TERMINAUX

TÉLÉPHONE IP 2LIGNES POE

Code : **9420132**

Modèle : **TFI-401**

Description
Le TFI-401 est la nouvelle référence des téléphones IP de base pour les gammes ACCURO et LIVERO. Équipé d'un écran graphique rétroéclairé noir et blanc, le téléphone TFI-401 offre une visibilité extraordinaire de toutes les informations relatives aux appels et alarmes de nos systèmes.
Il s'agit d'un téléphone facile à utiliser qui permet l'identification des alertes et leur origine, les appels en attente, le journal des appels, les transferts d'appels (répondus et non répondus), le contrôle du volume et permet la communication vocale avec les points d'appel.
Situé dans l□office infirmier ou poste de contrôle, le TFI-401 dispose également d'un indicateur LED visible sous tous les angles, même à grande distance, destiné à notifier les appels entrants, les appels en cours et les messages en attente. Il dispose également de quatre touches dynamiques facilement configurables pour automatiser les fonctions téléphoniques en un seul clic, en plus des cinq touches de fonction fixes que l'utilisateur peut utiliser de manière simple et intuitive. D'autre part, son système d'alimentation PoE (Power-over-Ethernet) garantit une faible consommation d'énergie et une installation facile.

Caractéristiques principales:
- Deux comptes SIP (Session Initiation Protocol)
- Faible consommation d'énergie (PoE)
- Affichage graphique rétro-éclairé
-Notification acoustico-lumineuse des appels
- Quatre touches dynamiques et cinq touches de fonction fixes

CODIGO/CODE	9420132
MODELO /MODEL/MODELE	TFI-401
CARACTERISTICAS AUDIO AUDIO FEATURE AUDIO FEATURE	Codecs: · G.711 a-law, μ-law · G.722 (wideband) · G.726, g.729ab, gsm 6.10 (fr) · 10 built-in assignable ringtones · Comfort noise generator (cng) · Voice activity detection (vad)
RED Y SEGURIDAD NETWORK & SECURITY RESEAU ET SECURITÉ	· Transport Layer Security (TLS) · SRTP (RFC3711), SIPS, SRTCP · VLAN · IEEE 802.1X · LLDP-MED · Web interface password protection · 2 SIP identities/accounts · XML Browser · Call lists for dialed, received, missed calls · Directory with 250 entries · Languages: English, French, Spanish · Additional language support via provisioning · In-band DTMF/out-of-band DTMF/SIP INFO DTMF · Interoperable with all major IP-PBX platforms

CODIGO/CODE	9420132
MODELO /MODEL/MODELE	TFI-401
CARACTERISTICAS LLAMADA CALL FEATURES CARACTERISTIQUES DES APPELS	· Speed dialing · URL dialing · Local dial plan · Automatic Redial on Busy · Call completion (busy/unreachable) (2) · Caller identification · Call waiting / Call blocking (deny list) · Blocking of anonymous calls (2) · Auto answer · Lists of missed, received and dialed calls · Hold · Music on hold (2) · Handling of up to 2 simultaneous calls · Blind and attended transfer · Call forwarding · 3-way conference on the phone · Call pickup (2) · Call Park, call unpark (2) · Multicast paging
CARACTERISTICAS FISICAS HARWARE HARWARE	· Dimensions: 205 x 161 x 32 mm (w/o foot stand) · Dimensions: 205 x 161 x 120 mm (with foot stand) · Handset: RJ-4P4C · Headset: RJ-4P4C · Hearing aid compatible (HAC) handset · Power: PoE or 5V DC power adapter (1), · Environmental Conditions: · Ambient temperature: 0° to 35° C (32° to 95° F) · Non-operating temperature: –10 °C to 45 °C · Relative humidity: 5% to 95% noncondensing · Included in delivery: · Base phone unit · Foot stand · Handset with cord · Ethernet cable · Quick Installation Guide · Color: black