

# 942 TERMINAUX

## TÉLÉPHONE IP 6 LIGNES, TFT 2,7 □ BLANC



Code : **9420134**

Modèle : **TFI-403**

### Description

The TFI-403 is a professional desktop phone and a cost-effective entry-level device into the world of VoIP telephony. An advanced IP phone, the TFI-403 features a high-resolution colour display that is second to none in its price segment and also features a unique and innovative brightness and proximity sensor.

The sensor reacts as soon as the user's hand nears the display or the function keys of the IP phone and then displays frequently used features and called numbers. In addition, the sensor ensures that the brightness of the telephone display is always adjusted to the current lighting conditions in the room, reducing the carbon footprint of each device.

It is a easy-to-use telephone with functionality such as call ID, call waiting, call register, call transfers (attended and unattended) and volume control, which allow its use by the staff as a telephone control station for the reception of calls from the rooms.

In addition to the high-resolution colour display, the phone also has multi-colour LED function keys, an integrated gigabit switch and a USB port ensuring that the complete range of connectivity options are available.

Of course, the TFI-403 is available in both black and white.

This means that the phone can be perfectly adapted to a variety of business locations - whether office or practice.

The TFI-403 combines state-of-the-art technology, best voice quality and a clear design in one device - at an unbeatable price. This makes the perfect entry-level device in the world of professional IP telephony.

### Characteristics:

- High-resolution TFT display
- Integrated light sensor
- 3 self-labelling function keys
- Wideband hands-free talking (speakerphone)
- Digital Signal Processor (DSP) enhanced audio quality
- 2-port Gigabit Ethernet switch (RJ45)
- Power over Ethernet IEEE 802.3af, Class 2

CODE	9420134
MODEL	TFI-403
AUDIO FEATURE	Codecs: G.711 A-law, $\mu$ -law G.722 (wideband) G.726, G.729AB, GSM 6.10 (FR) Built-in assignable ringtones Comfort Noise Generator (CNG) Voice Activity Detection (VAD)
NETWORK & SECURITY	802.1X authentication and EAPOL Transport layer security (TLS) SRTP (RFC3711), SIPS, RTCP HTTPS server/client password-protected web interface VPN-support VLAN (IEEE 802.1Q) LLDP-MED, RTCP-XR SIP (RFC3261) HDCP, NTP HTTP/HTTPS/TFTP LDAP (Directory) Dual Stack IPv4 / IPv6
CALL FEATURES	Speed dialing URL dialing Local dial plan Automatic redial on busy Call completion (busy/unreachable) (2) Caller identification Call waiting Call blocking (deny list) Auto answer Hold Music on hold (2) Blind and attended transfer

CODE	9420134
MODEL	TFI-403
	<p>3-way conferencing on the phone</p> <p>Extension monitoring, call pickup (2)</p> <p>Call park, call unpark (2)</p> <p>Multicast paging</p> <p>DND mode (do not disturb)</p> <p>Keyboard lock</p> <p>Client matter code (CMC) (2)</p> <p>Unified Communications ready</p>
PHISICAL FEATURES	<p>Dimensions (approx.):</p> <p>205 x 185 x 40mm (LxWxD) w/o foot stand</p> <p>205 x 185 x 200/220mm (LxWxD) with foot stand</p> <p>Weight (approx.) device 710g, footstand 120g</p> <p>Input voltage: 5Vdc (SELV)</p> <p>Power supply: PoE or 5Vdc power adapter (1), 10 Watts</p> <p>Handset: 4P4C</p> <p>Headset: 4P4C Support for Snom EHS Advanced (1)</p> <p>Hearing -Aid compatible (HAC) headset</p> <p>1xUSB 2.0 host port, Type A</p> <p>Environmental conditions:</p> <p>Ambient temperature: 0°C to 35°C (32°F to 95°F)</p> <p>Storage temperature: -10°C to 45°C (14°F to 113°F)</p> <p>Humidity: 5% to 95% (non-condensing)</p> <p>Included in delivery:</p> <p>Phone unit</p> <p>Footstand</p> <p>Handset with cord</p> <p>Ethernet cable</p> <p>Colour: Black or white</p>