

## 949 TERMINAUX

## TÉLÉPHONE IP 6 LIGNES, TFT 2,7 🛮 BLANC



Code: 9420134

Modèle : TFI-403

## Description

Characteristics

The TFI-403 is a professional desktop phone and a cost-effective entry-level device into the world of VoIP telephony. An advanced IP phone, the TFI-403 features a high-resolution colour display that is second to none in its price segment and also features a unique and innovative brightness and proximity sensor.

The sensor reacts as soon as the user's hand nears the display or the function keys of the IP phone and then displays frequently used features and called numbers. In addition, the sensor ensures that the brightness of the telephone display is always adjusted to the current lighting conditions in the room, reducing the carbon footprint of each device.

It is a easy-to-use telephone with functionality such as call ID, call waiting, call register, call transfers (attended and unattended) and volume control, which allow its use by the staff as a telephone control station for the reception of calls from the rooms.

In addition to the high-resolution colour display, the phone also has multicolour LED function keys, an integrated gigabit switch and a USB port ensuring that the complete range of connectivity options are available. Of course, the TFI-403 is available in both black and white.

This means that the phone can be perfectly adapted to a variety of business locations - whether office or practice.

The TFI-403 combines state-of-the-art technology, best voice quality and a clear design in one device - at an unbeatable price. This makes the perfect entry-level device in the world of professional IP telephony.

Characteristics.
☐ High-resolution TFT display
☐ Integrated light sensor
3 self-labelling function keys
☐ Wideband hands-free talking (speakerphone)
$\hfill \square$ Digital Signal Processor (DSP) enhanced audio quality
2-port Gigabit Ethernet switch (RJ45)
Power over Ethernet IEEE 802 3af Class 2



CODE	9420134
MODEL	TFI-403
AUDIO FEATURE	Codecs:
	G.711 A-law, µ-law
	G.722 (wideband)
	G.726, G.729AB, GSM 6.10 (FR)
	Built-in assignable ringtones
	Comfort Noise Generator (CNG)
	Voice Activity Detection (VAD)
NETWORK & SECURITY	802.1X authentication and EAPOL
	Transport layer security (TLS)
	SRTP (RFC3711), SIPS, RTCP
	HTTPS server/client
	password-protected web interface
	VPN-support
	VLAN (IEEE 802.1Q)
	LLDP-MED, RTCP-XR
	SIP (RFC3261)
	HDCP, NTP
	HTTP/HTTPS/TFTP
	LDAP (Directory)
	Dual Stack IPv4 / IPv6
CALL FEATURES	Speed dialing
	URL dialing
	Local dial plan
	Automatic redial on busy
	Call completion (busy/unreachable) (2)
	Caller identification
	Call waiting
	Call blocking (deny list)
	Auto answer
	Hold
	Music on hold (2)
	Dlind and attended transfer



CODE	9420134
MODEL	TFI-403
	3-way conferecning on the phone
	Extension monitoring, call pickup (2)
	Call park, call unpark (2)
	Multicast paging
	DND mode (do not disturb)
	Keyboard lock
	Client matter code (CMC) (2)
	Unified Communications ready
PHISICAL FEATURES	Dimensions (approx.):
	205 x 185 x 40mm (LxWxD) w/o foot stand
	$205 \times 185 \times 200/220$ mm (LxWxD) with foot stand
	Weight (approx.) device 710g, footstand 120g
	Input voltage: 5Vdc (SELV)
	Power supply: PoE or 5Vdc power adapter (1), 10 Watts
	Handset: 4P4C
	Headset: 4P4C Support for Snom EHS Advanced (1)
	Hearing -Aid compatible (HAC) handset
	1xUSB 2.0 host port, Type A
	Environmental conditions:
	Ambient temperature: 0°C to 35°C (32°F to 95°F)
	Storage temperature: -10°C to 45°C (14°F to 113°F)
	Humidity: 5% to 95% (non-condensing)
	Included in delivery:
	Phone unit
	Footstand
	Handset with cord
	Ethernet cable
	Colour: Black or white